



Main

Range	Ultimate
Aesthetic name	Low profile
Product or component type	Switched socket
Device application	Power supply
Fixing mode	By screws
Socket number	2
Switch function	1-pole 1-way
Outlet poles configuration	2P + E
Colour tint	Chrome White
Rated current	13 A

Complementary

Device presentation	Complete product
Device mounting	Flush
Actuator	Rocker
Number of rocker	2
Outlet standard	BS 1363
Outlet standard deviation	British
Earth circuit	Standard earth
Surface finish	Brushed
Material	Steel
[Ue] rated operational voltage	230 V
Network type	AC
Network frequency	50/60 Hz
Connections - terminals	Screw terminal
IP degree of protection	IP20
Width	148 mm
Height	88 mm
Depth	30 mm

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.000 cm
Package 1 Width	9.700 cm
Package 1 Length	15.500 cm
Package 1 Weight	264.700 g
Unit Type of Package 2	CAR
Number of Units in Package 2	50
Package 2 Height	18.000 cm
Package 2 Width	42.500 cm
Package 2 Length	50.000 cm
Package 2 Weight	13.769 kg
Unit Type of Package 3	PAM
Number of Units in Package 3	1000

Package 3 Height	106.500 cm
Package 3 Width	120.000 cm
Package 3 Length	100.000 cm
Package 3 Weight	295.376 kg

Offer Sustainability

REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes

Contractual warranty

Warranty	18 months
----------	-----------