

EXIT3MLED



Fitting with proven long term reliability and performance. Range now includes an ISO fitting and Self-Test option.



SEEXIT3ML

PERFECT FOR OFFICE, COMMERCIAL AND INDUSTRIAL APPLICATIONS




### LED EMERGENCY EXIT BOX SIGNS

Low energy alternative to standard emergency exit signs

- Steel construction
- 3 hour maintained mode as standard which can also be configured for non maintained operation
- Facility for remote switching
- Diffuser on base: for added downward illumination of exit path
- Long life energy efficient LED light source eliminates lamp replacement cycle without compromising panel visibility distance
- Full range of alternative legend directional panels available
- LED charge light
- Battery test button (not on self test version)
- Viewing distance 32m
- 55 lumens in mains mode
- Fitting 5 year warranty, battery 1 year warranty
- Replacement battery code: EB4

Hole knockouts on each side of fitting



SEEXIT3ML

EXIT3MLED



EBLGDU



ISOEBLGDD



#### EXIT3MLED:

- Interchangeable polycarbonate signs directive down arrow exit legend included

#### EXIT3MLISO:

- Interchangeable polycarbonate ISO up arrow exit legend included

#### SEEXIT3ML:

- Automatic testing in accordance with EN 62034
- Interchangeable polycarbonate ISO up arrow exit legend included

- **Fittings** = M.O.M: 6 / O.P.Q: 6
- **Legends** = M.O.M: 1 / O.P.Q: 100

Code	Version	Colour	Wattage	Avg. Rated Life (Hrs)	IP Rating
EXIT3MLED	Exit Box With Signs Directive Down Arrow Legend	White	4W	30,000 hrs	IP20
EXIT3MLISO	Exit Box With ISO 7010 Up Arrow Legend				
SEEXIT3ML	Self Test With ISO 7010 Up Arrow Legend				

Code	Legend Version
EBLGD	Signs Directive Left Arrow Legend
EBLGDR	Signs Directive Right Arrow Legend
EBLGDU	Signs Directive Up Arrow Legend
ISOEBLGDL	ISO 7010 Left Arrow Legend
ISOEBLGDR	ISO 7010 Right Arrow Legend
ISOEBLGDU	ISO 7010 Up Arrow Legend
ISOEBLGDD	ISO 7010 Down Arrow Legend