

## making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

## IDPSS-W GRID-IT | GRID-IT RANGE | Rocker Switch Modules

Item Image	Wiring	Dimensions
	Live Neutral IN IN L IN N  CE BS EN 60669 20AX 250V- Double Pole L OUT N Live Neutral To To Load Load	Hemilton GRID-IT GDP 20AX Double Pole Rocker Module
Primary Range	GRID-IT	
Insert Type	20AX Double Pole Rocker Module	
Insert Colour	Satin Steel/White	
EAN13 Barcode	5051164149635	
Commodity Code	85363030	
Luckins TSI	387391092	
Dimensions(Nominal)	Module: Height = Width = Depth =	
Weight	43 GR	
Switched Poles	Double	
Current Rating	20AX	
Voltage	220/250V AC	
Maximum Load	20 Amp inductive	
Mains Frequency	50Hz	
IP Rating	IP2XD	
Contact Gap Minimum	3mm	
Terminal Capacity 1	5x1mm <sup>2</sup>	
Terminal Capacity 2	4x1.5mm <sup>2</sup>	
Terminal Capacity 3	2x2.5mm <sup>2</sup>	
Terminal Capacity 4	1x4mm² Multi-strand	
Terminal Capacity 5	lx6mm²	
Earth Terminal Capacity 1	6x1mm²	
Earth Terminal Capacity 2	5x1.5mm <sup>2</sup>	
Earth Terminal Capacity 3	3x2.5mm <sup>2</sup>	
Earth Terminal Capacity 4	2x4mm² Multi-strand	
Earth Terminal Capacity 5	lx6mm²	
Product Class 1	Face plate must be earthed	
Ambient Operating Temperature	-5° to +40°C	
Recommended Location	Internal Use Only	
Maximum Installation Altitude 2000m		
IDPSS-W - Grid-IT 20AX Double Pole Rocker Module Satin Steel/White		

IDPSS-W - Grid-IT 20AX Double Pole Rocker Module Satin Steel/White



Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

## **IDPSS-W** GRID-IT | GRID-IT RANGE | Rocker Switch Modules Standard/Approval BS EN 60669-1 It is the policy of the company to All products listed conform to current All accessories are manufactured improve products as part of our British or European standard and the under an accredited BS EN ISO 9001: development programme. Therefore, product information is correct at the 2015 Quality Management System. we reserve the right to alter designs time of going to press. and dimensions without prior notice. Illustrations and diagrams are Due to manufacturing processes we reproduced within the limitations of Correct as at 18 August 2021 12:42 PM cannot guarantee an exact colour reproduction and printing process and match and shadings of of certain E&OE are not binding. finishes. R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ T: +44 (0)1747 860088 F: +44 (0)1179 710414 E: info@hamilton-litestat.com www.hamilton-litestat.com Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84