IR212SS-W - Grid-IT 20AX 2 Way Rocker Module Satin Steel/White



making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

IR212SS-W

GRID-IT | GRID-IT RANGE | Rocker Switch Modules

Primary Range CRID-IT Insert Type 20AX 2 Way Rocker Module Insert Colour Satin Steel/White EAN13 Barcode SoSin6a(496)1 Commodity Code 85363030 Luckins TSI 387391665 Dimensions(Nominal) Module: Height = Width = Depth = Weight Weight 43 GR Switched Poles Single Current Rating 20AX Voltage 220/250V AC Maximum Load 20 Amp inductive Mains Frequency SOHz P Rating IP2XD Contact Gap Minimum 3mm Ierminal Capacity 1 Sxlmm² Ierminal Capacity 1 Sxlmm² Ierminal Capacity 4 2x4mm² Multi-strand Ierminal Capacity 4 2x4mm² Multi-strand Ierminal Capacity 5 Ix6mm² Earth Terminal Capacity 5 Ix6mm² Earth Terminal Capacity 3 Sxl.5mm² Earth Terminal Capacity 4 2x4mm² Multi-strand Ierminal Capacity 5 Ix6mm² Earth Terminal Capacity 5 Ix6mm² Earth Terminal Capacity 3 Sxl.5mm² Earth Terminal Capacity 4 2x4mm² Multi-strand Ierminal Capacity 5 Ix6mm² Earth Terminal Capacity 3 Sxl.5mm² Earth Terminal Capacity 4 2x4mm² Multi-strand Earth Terminal Capacity 5 Ix6mm² Earth Terminal Capacity 6 Ix6mm² Earth Terminal Capacity 6 Ix6mm² Earth Terminal Capacity 6 Ix6mm² Earth Terminal Capacity 7 Ix6mm² Earth Terminal Capacity 8 Ix6mm² Earth Terminal Capacity 9 Ix6mm² Earth Termina	Item Image	Wiring	Dimensions
Insert Type		See and the second seco	GRID-IT GR212 20AX 2 Way Rocker Module
Insert Colour	Primary Range	GRID-IT	
EAN13 Barcode 5051164149611 Commodity Code 85363030 Luckins TSI 387391665 Dimensions(Nominal) Module: Height = Width = Depth = Weight 43 GR Switched Poles Single Current Rating 20AX Voltage 220/250V AC Maximum Load 20 Amp inductive Mains Frequency 50Hz IP Rating IPZXD Contact Gap Minimum 3mm Terminal Capacity 1 5xlmm² Terminal Capacity 2 4xl.5mm² Terminal Capacity 3 2x2.5mm² Terminal Capacity 4 2x4mm² Multi-strand Terminal Capacity 5 1x6mm² Earth Terminal Capacity 2 5xl.5mm² Earth Terminal Capacity 3 3x2.5mm² Earth Terminal Capacity 4 2x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Product Class 1 Face plate must be earthed Ambient Operating Temperature -5° to +40°C		20AX 2 Way Rocker Module	
Commodity Code 85363030 Luckins TSI 387391665 Dimensions(Nominal) Module: Height = Width = Depth = Weight 43 GR Switched Poles Single Current Rating 20AX Voltage 220/250V AC Maximum Load 20 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5xlmm² Terminal Capacity 2 4x1.5mm² Terminal Capacity 3 2x2.5mm² Terminal Capacity 4 2x4mm² Multi-strand Terminal Capacity 1 6xlmm² Earth Terminal Capacity 1 6xlmm² Earth Terminal Capacity 3 3x2.5mm² Earth Terminal Capacity 4 2x4mm² Multi-strand Earth Terminal Capacity 4 2x4mm² Multi-strand Earth Terminal Capacity 4 5x1.5mm² Earth Terminal Capacity 4 5x1.5mm² Earth Terminal Capacity 5 1x6mm² Earth Terminal Capacity 4 5x1.5mm² Earth Terminal Capacity 5 1x6mm² Earth Terminal Capacity 4 5x4.5mm² Earth Terminal Capacity 5 1x6mm² Earth Terminal Capacity 5 1x6mm² Earth Terminal Capacity 5 1x6mm² Product Class 1 Face plate must be earthed Ambient Operating Temperature -5° to +40°C			
Luckins TSI 387391665 Dimensions(Nominal) Module: Height = Width = Depth = Weight 43 GR Switched Poles Single Current Rating 20AX Voltage 220/250V AC Maximum Load 20 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5x1mm² Terminal Capacity 2 4x1.5mm² Terminal Capacity 3 2x2.5mm² Terminal Capacity 4 2x4mm² Multi-strand Terminal Capacity 5 1x6mm² Earth Terminal Capacity 1 6x1mm² Earth Terminal Capacity 5 1x6mm² Earth Terminal Capacity 4 2x4mm² Multi-strand Terminal Capacity 5 1x6mm² Earth Terminal Capacity 1 5x1.5mm² Earth Terminal Capacity 2 5x1.5mm² Earth Terminal Capacity 4 2x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Earth Terminal Capacity 4 2x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Earth Terminal Capacity 5 1x6mm² Earth Terminal Capacity 4 2x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Earth Terminal Capacity 5 1x6mm² Earth Terminal Capacity 5 1x6mm² Face plate must be earthed Ambient Operating Temperature -5° to +40°C	EAN13 Barcode	5051164149611	
Dimensions(Nominal) Module: Height = Width = Depth = Weight 43 GR Switched Poles Single Current Rating 20AX Voltage 220/250V AC Maximum Load 20 Amp inductive Mains Frequency IP Rating Contact Gap Minimum Ierminal Capacity 1 Sxlmm² Terminal Capacity 2 4xl.5mm² Terminal Capacity 3 Terminal Capacity 4 1erminal Capacity 5 Ikafmm² Earth Terminal Capacity 1 Sxlmm² Earth Terminal Capacity 1 Sxlmm² Multi-strand Ierminal Capacity 5 Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 4 Earth Terminal Capacity 5 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 5 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 5 Ixafmm² Earth Terminal Capacity 5 Face plate must be earthed Ambient Operating Temperature -5° to +40°C	Commodity Code	85363030	
Weight 43 GR Switched Poles Single Current Rating 20AX Voltage 220/250V AC Maximum Load 20 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5x1mm² Terminal Capacity 2 4x1.5mm² Terminal Capacity 3 2x2.5mm² Terminal Capacity 4 2x4mm² Multi-strand Terminal Capacity 5 1x6mm² Earth Terminal Capacity 1 6x1mm² Earth Terminal Capacity 5 1x6mm² Earth Terminal Capacity 5 2x1.5mm² Earth Terminal Capacity 6 5x1.5mm² Earth Terminal Capacity 7 5x1.5mm² Earth Terminal Capacity 8 5x1.5mm² Earth Terminal Capacity 9 5x1.5mm² Earth Terminal Capacity 1 5x1.5mm² Earth Terminal Capacity 3 5x2.5mm² Earth Terminal Capacity 5 1x6mm² Product Class 1 Face plate must be earthed Ambient Operating Temperature -5° to +40°C	LuckinsTSI	387391665	
Switched Poles Current Rating 20AX Voltage 220/250V AC Maximum Load 20 Amp inductive Mains Frequency IP Rating IPZXD Contact Gap Minimum Terminal Capacity 1 Terminal Capacity 2 Terminal Capacity 3 Terminal Capacity 4 Terminal Capacity 4 Terminal Capacity 5 Terminal Capacity 5 Terminal Capacity 1 Terminal Capacity 4 Terminal Capacity 5 Terminal Capacity 5 Terminal Capacity 5 Terminal Capacity 6 Salmm² Terminal Capacity 6 Salmm² Terminal Capacity 6 Salmm² Terminal Capacity 1 Salmm² Terminal Capacity 5 Terminal Capacity 5 Terminal Capacity 6 Salmm² Terminal Capacity 1 Salmm² Terminal Capacity 2 Salmm² Terminal Capacity 3 Terminal Capacity 3 Terminal Capacity 4 Terminal Capacity 5 Teach Terminal Capacity 4 Terminal Capacity 5 Terminal Capacity 5 Terminal Capacity 6 Terminal Capacity 6 Terminal Capacity 7 Terminal Capacity 8 Terminal Capacity 9 Terminal	Dimensions(Nominal)	Module: Height = Width = Depth =	
Current Rating 20AX Voltage 220/250V AC Maximum Load 20 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5xlmm² Terminal Capacity 2 4xl.5mm² Terminal Capacity 3 2x2.5mm² Terminal Capacity 4 2x4mm² Multi-strand Terminal Capacity 5 1x6mm² Earth Terminal Capacity 1 6xlmm² Earth Terminal Capacity 2 5xl.5mm² Earth Terminal Capacity 3 1x6mm² Earth Terminal Capacity 4 5xl.5mm² Earth Terminal Capacity 5 1x6mm² Earth Terminal Capacity 6 5xl.5mm² Earth Terminal Capacity 7 5xl.5mm² Earth Terminal Capacity 8 2x4mm² Multi-strand Earth Terminal Capacity 9 5xl.5mm² Face plate must be earthed Ambient Operating Temperature -5° to +40°C	Weight	43 GR	
Voltage 220/250V AC Maximum Load 20 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5x1mm² Terminal Capacity 2 4x1.5mm² Terminal Capacity 3 2x2.5mm² Terminal Capacity 4 2x4mm² Multi-strand Terminal Capacity 5 1x6mm² Earth Terminal Capacity 1 6x1mm² Earth Terminal Capacity 2 5x1.5mm² Earth Terminal Capacity 3 3x2.5mm² Earth Terminal Capacity 4 2x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Earth Terminal Capacity 4 2x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Earth Terminal Capacity 5 1x6mm² Earth Terminal Capacity 5 1x6mm² Face plate must be earthed Ambient Operating Temperature -5° to +40°C	Switched Poles	Single	
Maximum Load 20 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5xlmm² Terminal Capacity 2 4x1.5mm² Terminal Capacity 3 2x2.5mm² Terminal Capacity 4 2x4mm² Multi-strand Terminal Capacity 5 1x6mm² Earth Terminal Capacity 1 6xlmm² Earth Terminal Capacity 2 5x1.5mm² Earth Terminal Capacity 3 3x2.5mm² Earth Terminal Capacity 4 5x1.5mm² Earth Terminal Capacity 5 5x1.5mm² Earth Terminal Capacity 3 3x2.5mm² Earth Terminal Capacity 4 2x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Product Class 1 Face plate must be earthed Ambient Operating Temperature -5° to +40°C	Current Rating	20AX	
Mains Frequency IP Rating Contact Gap Minimum Terminal Capacity 1 Terminal Capacity 2 Terminal Capacity 3 Terminal Capacity 4 Terminal Capacity 4 Terminal Capacity 5 Ix6mm² Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 3 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 5 Earth Terminal Capacity 5 Earth Terminal Capacity 6 Earth Terminal Capacity 7 Earth Terminal Capacity 8 Earth Terminal Capacity 8 Earth Terminal Capacity 9	Voltage	220/250V AC	
IP Rating Contact Gap Minimum Terminal Capacity 1 Terminal Capacity 2 4x1.5mm² Terminal Capacity 3 2x2.5mm² Terminal Capacity 4 2x4mm² Multi-strand Terminal Capacity 5 Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 5 Earth Terminal Capacity 6 Earth Terminal Capacity 6 Earth Terminal Capacity 7 Earth Terminal Capacity 8 Earth Terminal Capacity 9 Earth	Maximum Load	•	
Contact Gap Minimum Terminal Capacity 1 Terminal Capacity 2 4x1.5mm² Terminal Capacity 3 2x2.5mm² Terminal Capacity 4 2x4mm² Multi-strand Terminal Capacity 5 Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 3 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 5 Earth Terminal Capacity 5 Earth Terminal Capacity 5 Earth Terminal Capacity 6 Earth Terminal Capacity 7 Earth Terminal Capacity 8 Earth Terminal Capacity 9 Earth Terminal Capacity 9 Earth Terminal Capacity 5 Earth Terminal Capacity 6 Earth Terminal Capacity 6 Earth Terminal Capacity 7 Earth Terminal Capacity 9 Earth Terminal C	Mains Frequency	50Hz	
Terminal Capacity 2 4x1.5mm² Terminal Capacity 3 2x2.5mm² Terminal Capacity 4 2x4mm² Multi-strand Terminal Capacity 5 1x6mm² Earth Terminal Capacity 1 6x1mm² Earth Terminal Capacity 2 5x1.5mm² Earth Terminal Capacity 3 3x2.5mm² Earth Terminal Capacity 4 2x4mm² Multi-strand Earth Terminal Capacity 5 5x1.5mm² Earth Terminal Capacity 4 2x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Product Class 1 Face plate must be earthed Ambient Operating Temperature -5° to +40°C	IP Rating	IP2XD	
Terminal Capacity 2 4x1.5mm² Terminal Capacity 3 2x2.5mm² Terminal Capacity 4 2x4mm² Multi-strand Terminal Capacity 5 1x6mm² Earth Terminal Capacity 1 6x1mm² Earth Terminal Capacity 2 5x1.5mm² Earth Terminal Capacity 3 3x2.5mm² Earth Terminal Capacity 4 2x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Earth Terminal Capacity 5 1x6mm² Product Class 1 Face plate must be earthed Ambient Operating Temperature -5° to +40°C	Contact Gap Minimum	3mm	
Terminal Capacity 3 2x2.5mm² Terminal Capacity 4 2x4mm² Multi-strand Terminal Capacity 5 1x6mm² Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 5 1x6mm² Earth Terminal Capacity 5 1x6mm² Product Class 1 Face plate must be earthed Ambient Operating Temperature -5° to +40°C	Terminal Capacity 1	5x1mm ²	
Terminal Capacity 4 Zx4mm² Multi-strand Terminal Capacity 5 Ix6mm² Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 5 Ix6mm² Earth Terminal Capacity 5 Ix6mm² Product Class 1 Ambient Operating Temperature Zx4mm² Multi-strand Face plate must be earthed -5° to +40°C	Terminal Capacity 2		
Terminal Capacity 5 1x6mm² Earth Terminal Capacity 1 6x1mm² Earth Terminal Capacity 2 5x1.5mm² Earth Terminal Capacity 3 3x2.5mm² Earth Terminal Capacity 4 2x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Product Class 1 Face plate must be earthed Ambient Operating Temperature -5° to +40°C	Terminal Capacity 3	2x2.5mm ²	
Earth Terminal Capacity 1 6x1mm² Earth Terminal Capacity 2 5x1.5mm² Earth Terminal Capacity 3 3x2.5mm² Earth Terminal Capacity 4 2x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Product Class 1 Face plate must be earthed Ambient Operating Temperature -5° to +40°C	Terminal Capacity 4	2x4mm² Multi-strand	
Earth Terminal Capacity 2 5x1.5mm² Earth Terminal Capacity 3 3x2.5mm² Earth Terminal Capacity 4 2x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Product Class 1 Face plate must be earthed Ambient Operating Temperature -5° to +40°C	Terminal Capacity 5		
Earth Terminal Capacity 3 3x2.5mm² Earth Terminal Capacity 4 2x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Product Class 1 Face plate must be earthed Ambient Operating Temperature -5° to +40°C	Earth Terminal Capacity 1	6x1mm²	-
Earth Terminal Capacity 4 2x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Product Class 1 Face plate must be earthed Ambient Operating Temperature -5° to +40°C	Earth Terminal Capacity 2		
Earth Terminal Capacity 5 1x6mm² Product Class 1 Face plate must be earthed Ambient Operating Temperature -5° to +40°C			
Product Class 1 Face plate must be earthed Ambient Operating Temperature -5° to +40°C			
Ambient Operating Temperature -5° to +40°C			
	Recommended Location	Internal Use Only	
Maximum Installation Altitude 2000m	Maximum Installation Altitude	2000m	

IR212SS-W - Grid-IT 20AX 2 Way Rocker Module Satin Steel/White



Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

IR212SS-W GRID-IT | GRID-IT RANGE | Rocker Switch Modules Standard/Approval BS EN 60669-1 It is the policy of the company to All products listed conform to current All accessories are manufactured improve products as part of our British or European standard and the under an accredited BS EN ISO 9001: development programme. Therefore, product information is correct at the 2015 Quality Management System. we reserve the right to alter designs time of going to press. and dimensions without prior notice. Illustrations and diagrams are Due to manufacturing processes we reproduced within the limitations of Correct as at 18 August 2021 01:04 PM cannot guarantee an exact colour reproduction and printing process and match and shadings of of certain E&OE are not binding. finishes. R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ T: +44 (0)1747 860088 F: +44 (0)1179 710414 E: info@hamilton-litestat.com www.hamilton-litestat.com Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84