

## making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

### IR21SS-B

## GRID-IT | GRID-IT RANGE | Rocker Switch Modules

Primary Range GRID-IT Insert Type Insert Colour EAN13 Barcode Commodity Code Luckins TSI Dimensions(Nominal) Dimensions(Nominal) Module: Height = Width = Depth = Weight Weight Single  GRID-IT Insert Type Insert Colour Satin Steel/Black EAN13 Barcode Sol7504070991 Commodity Code Luckins TSI J91568170 Dimensions(Nominal) Module: Height = Width = Depth = Weight Single	Т
Insert Type 10AX 2 Way Rocker Module Insert Colour Satin Steel/Black EAN13 Barcode 5017504070991 Commodity Code 85363010 Luckins TSI 391568170 Dimensions(Nominal) Module: Height = Width = Depth = Weight 43 GR Switched Poles Single	
Insert Colour  Satin Steel/Black  EAN13 Barcode  5017504070991  Commodity Code  85363010  Luckins TSI  391568170  Dimensions(Nominal)  Module: Height = Width = Depth =  Weight  43 GR  Switched Poles  Single	
EAN13 Barcode         5017504070991           Commodity Code         85363010           Luckins TSI         391568170           Dimensions(Nominal)         Module: Height = Width = Depth =           Weight         43 GR           Switched Poles         Single	
Commodity Code85363010Luckins TSI391568170Dimensions(Nominal)Module: Height = Width = Depth =Weight43 GRSwitched PolesSingle	
Luckins TSI391568170Dimensions(Nominal)Module: Height = Width = Depth =Weight43 GRSwitched PolesSingle	
Dimensions(Nominal)Module: Height = Width = Depth =Weight43 GRSwitched PolesSingle	
Weight 43 GR Switched Poles Single	
Switched Poles Single	
3	
Current Rating 10AX	
Voltage 220/250V AC	
Maximum Load 10 Amp inductive	
Mains Frequency 50Hz	
IP Rating IP2XD	
Contact Gap Minimum 3mm	
Terminal Capacity 1 5x1mm <sup>2</sup>	
Terminal Capacity 2 4x1.5mm <sup>2</sup>	
Terminal Capacity 3 1x2.5mm <sup>2</sup>	
Terminal Capacity 4 1x4mm² Multi-strand	
Terminal Capacity 5 1x6mm <sup>2</sup>	
Earth Terminal Capacity 1 5x1mm <sup>2</sup>	
Earth Terminal Capacity 2 4x1.5mm <sup>2</sup>	
Earth Terminal Capacity 3 3x2.5mm <sup>2</sup>	
Earth Terminal Capacity 4 1x4mm² Multi-strand	
Earth Terminal Capacity 5 1x6mm <sup>2</sup>	
Product Class 1 Face plate must be earthed	
Ambient Operating Temperature -5° to +40°C	
Recommended Location Internal Use Only	
Maximum Installation Altitude 2000m	

IR21SS-B - Grid-IT 10AX 2 Way Rocker Module Satin Steel/Black



# Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

#### IR21SS-B GRID-IT | GRID-IT RANGE | Rocker Switch Modules Standard/Approval BS EN 60669-1 It is the policy of the company to All products listed conform to current All accessories are manufactured improve products as part of our British or European standard and the under an accredited BS EN ISO 9001: development programme. Therefore, product information is correct at the 2015 Quality Management System. we reserve the right to alter designs time of going to press. and dimensions without prior notice. Illustrations and diagrams are Due to manufacturing processes we reproduced within the limitations of Correct as at 18 August 2021 01:11 PM cannot guarantee an exact colour reproduction and printing process and match and shadings of of certain E&OE are not binding. finishes. R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ T: +44 (0)1747 860088 F: +44 (0)1179 710414 E: info@hamilton-litestat.com www.hamilton-litestat.com Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84