



G9, G4, GY6.35

1.5W G4 LED Lamp

Kosnic's Home range of LED products brings the energy saving capabilities of LED technology to the home. The range is both beautiful and functional while offering lamps that deliver huge energy savings over filament lamps without compromising on brightness. The lamps can quickly replace filament products in general lighting applications, and once in place rapid payback is achieved.

KLED1.5CPL/G4-N30 ()

Specification

Voltage (eg 220-240 Vac 50/60Hz)	12Vdc
Current (mA)	125
Rated Power (W)	1.5
CCT Words	Warm White
CCT (K)	3000
L70B50 Lifetime (h)	15000
Total Luminous Flux (lm)	140
Power Factor	1
Blue Light Hazard	RG1
Glow wire temperature(°C)	650
Dimensions L x W x D (mm)	37* ϕ 10mm
Weight (kg)	0.002
Ambient Temperature Range (°C)	-20 to 40
Depth (mm)	10

Light Source Specification

Lighting Technology Used	LED
Directional / Non Directional (DLS/NDLS)	NDLS
Light Source Cap Type (or other interface)	G4
Mains / Non-Mains (MLS/NMLS)	NMLS
Connected Light source (Y/N)	N
Colour Tunable Light Source (Y/N)	N
High Luminance Light Source (Y/N)	N
Anti-Glare Shield (Y/N)	N
Dimmable (Y/N/Specific dimmer)	N
Energy Consumption in on-mode (kWh/1000H)	2
Energy Efficiency Class (NEW FORMULA)	F
Useful Luminous Flux (lm)	140
Beam Angle correspondence (in 360°/120°/90°)	in 360°

CCT	3000
On-Mode Power (Pon) (W)	1.5
Standby Power (Psb) (W)	0
Networked Standby Power (Pnet) (W)	N/A
CRI	82
CRI (min)	80
CRI (max)	84
Height (mm)	37
Width (mm)	10
Depth (mm)	10
Claim of Equivalent Power? (Y/N)	Y
Equivalent Power (W)	15
Chromaticity Co-Ordinates (X)	0.434
Chromaticity Co-Ordinates (Y)	0.404
Peak Luminous Intensity (DLS) (cd)	N/A
Beam Angle (DLS)	N/A
Beam Angle (min)(DLS)	N/A
Beam Angle (max) (DLS)	N/A
R9 CRI (LED/OLED)	17
Survival Factor (x.xx)	0.9
Lumen Maintenance Factor (x.xx)	0.93
Displacement Factor	N/A
Colour Consistency in Mcadam Ellipses (Mains LED/OLED)	N/A
LED light source replaces fluorescent without integrated ballast of particular wattage (Mains LED/OLED) (Y/N)	N/A
Replacement W Claim (Mains LED/OLED) (W)	N/A
Flicker metric (pst LM) (x,x)	N/A
Stroboscopic effect metric (SVM) (x,x)	N/A

Technical Drawings

