



DD, T5C CFL Lamp

40w Plug-in fluorescent circular lamp

Kosnic's EXUN products offer a comprehensive range of compact fluorescent lamps and fluorescent tubes with premium specifications. Designed for use in commercial and industrial settings, such as offices, warehouses and supermarkets, the lamps deliver a high lumen to wattage ratio and are extremely robust and durable

KFT40STC/4P-840 ()

Specification

Rated Power (W)	40
CCT Words	Cool White
CCT (K)	4000K
Nominal Lifetime (h)	15000
L70B50 Lifetime (h)	15000
Depth (mm)	16

Light Source Specification

Lighting Technology Used	FL T5 circular
Directional / Non Directional (DLS/NDLS)	NDLS
Light Source Cap Type (or other interface)	2GX13
Mains / Non-Mains (MLS/NMLS)	NMLS
Connected Light source (Y/N)	N
Colour Tunable Light Source (Y/N)	N
High Luminance Light Source (Y/N)	N
Anti-Glare Shield (Y/N)	N
Dimmable (Y/N/Specific dimmer)	N
Energy Consumption in on-mode (kWh/1000H)	40
Energy Efficiency Class (NEW FORMULA)	G
Useful Luminous Flux (lm)	3400
Beam Angle correspondence (in 360°/120°/90°)	360
CCT	4000K
On-Mode Power (Pon) (W)	40
Standby Power (Psb) (W)	0
Networked Standby Power (Pnet) (W)	N/A
CRI	83
CRI (min)	80
CRI (max)	85
Height (mm)	299

Width (mm)	16
Depth (mm)	16
Claim of Equivalent Power? (Y/N)	N
Equivalent Power (W)	N/A
Chromaticity Co-Ordinates (X)	0.38
Chromaticity Co-Ordinates (Y)	0.38

Technical Drawings

