



## DD, T5C CFL Lamp

### 55w Plug-in fluorescent circular lamp

Kosnic's EXUN products offer a comprehensive range of compact fluorescent lamps and fluorescent tubes with premium specifications. Designed for use in commercial and industrial settings, such as offices, warehouses and supermarkets, the lamps deliver a high lumen to wattage ratio and are extremely robust and durable

**KFT55STC/4P-840** ( )

## Specification

Rated Power (W)	55
CCT Words	Cool White
CCT (K)	4000K
Nominal Lifetime (h)	15000
L70B50 Lifetime (h)	15000
Depth (mm)	16

## Light Source Specification

Lighting Technology Used	FL T5 circular
Directional / Non Directional (DLS/NDLS)	NDLS
Light Source Cap Type (or other interface)	2GX13
Mains / Non-Mains (MLS/NMLS)	NMLS
Connected Light source (Y/N)	N
Colour Tunable Light Source (Y/N)	N
High Luminance Light Source (Y/N)	N
Anti-Glare Shield (Y/N)	N
Dimmable (Y/N/Specific dimmer)	N
Energy Consumption in on-mode (kWh/1000H)	55
Energy Efficiency Class (NEW FORMULA)	G
Useful Luminous Flux (lm)	4300
Beam Angle correspondence (in 360°/120°/90°)	360
CCT	4000K
On-Mode Power (Pon) (W)	55
Standby Power (Psb) (W)	0
Networked Standby Power (Pnet) (W)	N/A
CRI	83
CRI (min)	80
CRI (max)	85
Height (mm)	299

Width (mm)	16
Depth (mm)	16
Claim of Equivalent Power? (Y/N)	N
Equivalent Power (W)	N/A
Chromaticity Co-Ordinates (X)	0.38
Chromaticity Co-Ordinates (Y)	0.38

## Technical Drawings

