

## LED NCF IP65

- LED Non-Corrosive luminaire, highly efficient, energy saving and maintenance free
- Designed to directly replace traditional twin and single body T8 & T5 fluorescent luminaires
- Impact resistant polycarbonate body and frosted polycarbonate diffuser
- Anti-tamper grade 316 stainless steel clips and locking screws supplied as standard
- Push-fit, loop in-out terminal block
- Luminaire efficacy up to 105 Lumen/Watt
- IP/IK Rating: IP65/IK08
- Colour temperature: 5000K
- Colour rendering index: >80
- Rated life (L70): 50,000 hours
- Operating temperature: -20°C to 45°C (Amb.)
- Emergency 3 hour maintained versions available. Self test button function fitted as standard
- Ideal for: Car parks, warehouse, manufacturing, workshops, food storage areas, retail, external canopies and other industrial applications



**5 YEAR**  
WARRANTY

**LED**

**IP65**

**EM3** | EMERGENCY MAINTAINED 3 HOURS

Part No.	Description	Wattage	Measurement L x W x H	Lumen Output	IP Rating	Power Factor	Colour Temperature
<b>Standard</b>							
LXNCF112LEDCW	LED 2ft Single, Non-Corrosive	1x12W	632 x 85 x 81mm	1260Lm	IP65	> 0.90	5000K
LXNCF124LEDCW	LED 4ft Single, Non-Corrosive	1x24W	1232 x 85 x 81mm	2520Lm	IP65	> 0.90	5000K
LXNCF140LEDCW	LED 5ft Single, Non-Corrosive	1x40W	1532 x 85 x 81mm	4200Lm	IP65	> 0.90	5000K
LXNCF148LEDCW	LED 6ft Single, Non-Corrosive	1x48W	1832 x 85 x 81mm	5040Lm	IP65	> 0.90	5000K
LXNCF212LEDCW	LED 2ft Twin, Non-Corrosive	2x12W	632 x 103 x 81mm	2520Lm	IP65	> 0.90	5000K
LXNCF224LEDCW	LED 4ft Twin, Non-Corrosive	2x24W	1232 x 103 x 81mm	5040Lm	IP65	> 0.90	5000K
LXNCF240LEDCW	LED 5ft Twin, Non-Corrosive	2x40W	1532 x 103 x 81mm	8400Lm	IP65	> 0.90	5000K
LXNCF248LEDCW	LED 6ft Twin, Non-Corrosive	2x48W	1832 x 103 x 81mm	10080Lm	IP65	> 0.90	5000K
<b>Emergency</b>							
LXNCF124LEDCWEM3	LED 4ft Single, Non-Corrosive, EM3	1x24W	1232 x 85 x 81mm	2520Lm	IP65	> 0.90	5000K
LXNCF140LEDCWEM3	LED 5ft Single, Non-Corrosive, EM3	1x40W	1532 x 85 x 81mm	4200Lm	IP65	> 0.90	5000K
LXNCF148LEDCWEM3	LED 6ft Single, Non-Corrosive, EM3	1x48W	1832 x 85 x 81mm	5040Lm	IP65	> 0.90	5000K
LXNCF212LEDCWEM3	LED 2ft Twin, Non-Corrosive, EM3	2x12W	632 x 103 x 81mm	2520Lm	IP65	> 0.90	5000K
LXNCF224LEDCWEM3	LED 4ft Twin, Non-Corrosive, EM3	2x24W	1232 x 103 x 81mm	5040Lm	IP65	> 0.90	5000K
LXNCF240LEDCWEM3	LED 5ft Twin, Non-Corrosive, EM3	2x40W	1532 x 103 x 81mm	8400Lm	IP65	> 0.90	5000K
LXNCF248LEDCWEM3	LED 6ft Twin, Non-Corrosive, EM3	2x48W	1832 x 103 x 81mm	10080Lm	IP65	> 0.90	5000K



Email [sales@luxna.co.uk](mailto:sales@luxna.co.uk)



Web [luxna-lighting.com](http://luxna-lighting.com)