

LED Panel 600

UGR<19 Low Glare

What is UGR<19? A luminaire which has a 'Unified Glare Rating' of 19 or less is suitable for use in applications where low glare lighting is required and areas where 'visual comfort' may be critical.

- High luminaire efficacy, 100 Lumen/Watt
- Energy savings up to 60% when replacing 4x18W T8 luminaires
- ECA compliant, 33W LED, 3300Lm
- Suitable for 25mm and 15mm T-bar ceilings
- Low glare, optical pattern diffuser for even light distribution
- Frame colour: White
- Standard non dimmable driver included
- Colour temperature: 4000K
- Colour rendering index: >80
- Rated Life (L70): 50,000 hours
- Options available:
 - Dimmable driver 1-10V & DALI: **LXLPF2-30D-48**
 - Dimmable driver Touch (Push) and DALI: **LXLPF2-900-DTD**
 - Emergency 3 hour remote pack: **LXLPF2-60-EM3**
 - Surface mounting frame: **LXPAN66SMB**
 - Wire suspension kit: **LXPAN663SCK**
- Ideal for: Offices, health care, education, museums and galleries, retail, laboratories, logistics and industry.



Part No.	Wattage	Measurement L x W x H	Lumen Output	IP Rating	Colour Temperature
LXPAN33LED66NW2/UGR19	33W	595 x 595 x 10.5mm	3300Lm	IP20	4000K



Email sales@luxna.co.uk



Web luxna-lighting.com