

LED Batten

- Highly efficient LED Batten, ideal energy saving replacement for T8 and T5 fluorescent
- Luminaire efficacy: Up to 100 Lumen/Watt
- Standard and high output versions to replace single and twin
- Steel base, white polycarbonate diffuser
- Fast push-fit, loop in-out terminal block
- Multiple rear and side cable entry points
- Tridonic LED driver and Emergency Pack
- IP Rating: IP20
- Colour temperature: 4000k
- Colour rendering index: >80
- Rated Life: 50,000 hours
- Operating temperature: -10°C to 40°C
- Options available:
 - Integral 3 Hour Emergency
 - Side mounting PIR Sensor



5 YEAR
WARRANTY

LED

IP20

EM3 EMERGENCY MAINTAINED 3 HOURS

Part No.	Description	Wattage	Measurement L x W x H	Lumen Output	IP Rating	Colour Temperature
Standard						
LXBAT425LED	LED 4ft Single Batten	25W	1220 x 65 x 75mm	2500Lm	IP20	4000K
LXBAT535LED	LED 5ft Single Batten	35W	1525 x 65 x 75mm	3500Lm	IP20	4000K
LXBAT643LED	LED 6ft Single Batten	43W	1745 x 65 x 75mm	4300Lm	IP20	4000K
LXBAT448LED	LED 4ft Twin Batten	48W	1220 x 65 x 75mm	4800Lm	IP20	4000K
LXBAT563LED	LED 5ft Twin Batten	63W	1525 x 65 x 75mm	6300Lm	IP20	4000K
LXBAT680LED	LED 6ft Twin Batten	80W	1745 x 65 x 75mm	8000Lm	IP20	4000K
Emergency						
LXBAT425LED/EM3	LED 4ft Single Batten, EM3	25W	1220 x 65 x 75mm	2500Lm	IP20	4000K
LXBAT535LED/EM3	LED 5ft Single Batten, EM3	35W	1525 x 65 x 75mm	3500Lm	IP20	4000K
LXBAT643LED/EM3	LED 6ft Single Batten, EM3	43W	1745 x 65 x 75mm	4300Lm	IP20	4000K
LXBAT448LED/EM3	LED 4ft Twin Batten, EM3	48W	1220 x 65 x 75mm	4800Lm	IP20	4000K
LXBAT563LED/EM3	LED 5ft Twin Batten, EM3	63W	1525 x 65 x 75mm	6300Lm	IP20	4000K
LXBAT680LED/EM3	LED 6ft Twin Batten, EM3	80W	1745 x 65 x 75mm	8000Lm	IP20	4000K



Email sales@luxna.co.uk



Web luxna-lighting.com