


LED Round and Square Panel Lights

- High output, luminaire efficacy up to 83 Lumen/Watt
- Ultra slim design suitable for limited depth ceiling voids
- Direct replacement alternatives for compact fluorescent fittings, low cost energy saving solution
- Instant start, product life not affected by frequent switching, ideal for use with occupancy controls
- Frame: Aluminium, white finish
- Remote 'plug-and-play' non-dimmable driver included
- Beam spread: 120°
- IP Rating: IP20
- Colour temperature: 3000K, 4000K and 6000K
- Colour rendering index: >80
- Rated Life (L70): 25,000 hours
- Options available:
 - Triac dimmable driver
 - Emergency 3 hour remote pack
- Ideal for corridors, waiting areas, offices, hotels, meeting rooms, restaurants, retail, education and leisure applications



2 YEAR
WARRANTY

LED

EM3 EMERGENCY
REMOTE PACK
AVAILABLE

Part No.	Description	Wattage	Measurement A x B x C*	Lumen Output			IP Rating	Colour Temperature		
				WW	NW	CW		WW	NW	CW
Round										
LXPLR6*	LED Round Panel Light	6W	120 x 108 x 22mm	320Lm	350Lm	350Lm	IP20	3000K	4000K	6000K
LXPLR9*	LED Round Panel Light	9W	145 x 132 x 22mm	550Lm	600Lm	600Lm	IP20	3000K	4000K	6000K
LXPLR12*	LED Round Panel Light	12W	172 x 158 x 22mm	820Lm	900Lm	900Lm	IP20	3000K	4000K	6000K
LXPLR18*	LED Round Panel Light	18W	225 x 210 x 22mm	1350Lm	1500Lm	1500Lm	IP20	3000K	4000K	6000K
LXPLR24*	LED Round Panel Light	24W	300 x 280 x 22mm	1850Lm	2000Lm	2000Lm	IP20	3000K	4000K	6000K
Square										
LXPLS6*	LED Square Panel Light	6W	120 / 120 x 105 x 22mm	320Lm	350Lm	350Lm	IP20	3000K	4000K	6000K
LXPLS9*	LED Square Panel Light	9W	145 / 145 x 130 x 22mm	550Lm	600Lm	600Lm	IP20	3000K	4000K	6000K
LXPLS12*	LED Square Panel Light	12W	172 / 172 x 155 x 22mm	820Lm	900Lm	900Lm	IP20	3000K	4000K	6000K
LXPLS18*	LED Square Panel Light	18W	225 / 225 x 210 x 22mm	1350Lm	1500Lm	1500Lm	IP20	3000K	4000K	6000K
LXPLS24*	LED Square Panel Light	24W	300 / 300 x 280 x 22mm	1850Lm	2000Lm	2000Lm	IP20	3000K	4000K	6000K
*Add WW for Warm White 3000K / NW for Neutral White 4000K / CW for Cool White 6000K				*Measurement: A= Outer, B= Cutout, C= Depth						
Optional dimmable drivers: LXPLRS6DD, LXPLRS9DD, LXPLRS12DD, LXPLRS18DD, (excluding 24W)										



Email sales@luxna.co.uk



Web luxna-lighting.com