


Flush Mounted Dry Lining Boxes Product Data Sheet

Product Range	MDLB (See sheet 2 for more detail)	<p>Image for reference only</p> 
Description	Flush mounted Dry Lining Box for use within stud walls.	
Key Features	<p>Wide securing outer flange.</p> <p>To suit board thickness from 1mm to 26mm</p> <p>Swivel snap out clamps</p> <p>Multiple Entry points</p> <p>Available with intumescent fire barrier pads</p>	
Dimensions	See sheet 2	
Material(s)	PVCu with Brass Inserts	
Compliance / Standards(s)	<p>CE & UKCA Marked</p> <p>Low Voltage Directive 2014/35/EU</p> <p>The Electrical Equipment (Safety) Regulations 2016</p> <p>BS 7671:2018</p> <p>BS 5733:2010+A1:2014</p> <p>BS 476-22:1987 when fitted with intumescent fire barrier pads</p>	
Packaging	Recyclable	

Sustainability

We work hard to ensure our products meet the highest standards and are totally committed to the environment and maximising our usage of recycled material within our manufacturing process.

This range is manufactured from PVC-U, a material that is 100% recyclable, is flame retardant and self-extinguishing.



Stock Code	Single / Twin Gang	Depth (mm)	Adjustment (mm)
MDLB3WH	Single	34	1-9
MDLB1WH	Single	34	6-14
MDLB7WH	Single	34	18-25
MDLB4WH	Twin	34	1-9
MDLB2WH	Twin	34	6-14
MDLB8WH	Twin	34	18-25
MDLB22WH	Dual Single	34	6-14
MDLB13WH	Single	25	1-9
MDLB14WH	Twin	25	1-9
MDLB29WH	Single	46	9-26
MDLB30WH	Twin	46	9-26