

Section 1: Identification of the substance/mixture & of the company / undertaking**1.1 Product Identifier****GLV400**

Product Name

Silver Galve.

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Paint.

1.3 Details of the supplier of the safety data sheet

Supplier

Specialised Wiring Accessories Ltd

Abbey Mills

Charfield Road

Kingswood

Wotton-Under-Edge

Gloucestershire GL12 8RL

Tel: +44 (0) 01453 844 333 (Monday to Friday 8am to 5.30pm)

Fax: +44 (0) 01453 842 224

E-mail: sales@swaonline.co.uk

Section 2: Hazard identification**2.1 Classification of the substance or mixture****Classification (EC1272/2008)****Physical hazards** Flam. Aerosol 1 - H222, H229**Health hazards** Skin Irrit. 2 - H315

Eye Irrit. 2 - H319

STOTE SE 3 - H335, H336

Environmental hazards Aquatic Chronic - H411**Human health**

Gas or vapour is harmful on prolonged exposure or in high concentrations, vapours and aerosol mists have a narcotic effect and may cause headache, fatigue, dizziness, and nausea.

Deliberately concentrating and inhaling the contents of this container is dangerous and can be fatal.

Environmental

The product is not expected to be hazardous to the environment.

Physicochemical

Aerosol containers can explode when heated, due to pressure build-up. The product is extremely flammable. When sprayed on naked flame or incandescent material the vapours can be ignited.

2.2 Label elements

Pictogram



Signal Word

Danger

Hazard statements

- H222 Extremely flammable aerosol.
- H229 Pressurised container; may burst if heated.
- H319 Causes serious eye irritation.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

- P210 Keep away from heat, hot surfaces, sparks, open flames, and other ignition sources. No smoking.
- P211 Do not spray on an open flame or other ignition source.
- P251 Pressurized container: Do not pierce or burn, even after use.
- P260 Do not breathe vapour / spray.
- P271 Use only outdoors or in a well-ventilated area.
- P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122°F.
- P102 Keep out of reach of children.
- P501 Dispose of contents/container in accordance with local regulations.

Supplemental label information EUH066 Repeated exposure may cause skin dryness or cracking.

Contains ACETONE, SOLVENT NAPHTHA (PETROLEUM), LIGHT AROM. ; LOW BOILING POINT NAPHTHA,

2.3 Other hazards

This product does not contain any substances classified as PBT or vPvB.

Section 3: Composition / information on ingredients

3.2 Mixtures

PETROLEUM GASES, LIQUEFIED; PETROLEUM GAS		Content: 30 - 60%
CAS-No: 68476-85-7	EC No: 270-704-2	
Classification Flam. Gas 1 - H220 Press. Gas, Liquefied - H280		

ACETONE		Content: 10 - 30%
CAS-No: 67-64-1	EC No: 200-662-2	REACH Registration Number: 01-2119471330-49
Classification Flam. Liq. 2 - H319 Eye. Irrit. - H319 STOTE SE3 - H336		

SOLVENT NAPHTHA (PETROLEUM), LIGHT AROM.; LOW BOILING POINT NAPHTHA		Content: 10 - 30%
CAS-No: 64742-95-6	EC No: 265-199-0	REACH Registration Number: 01-2119455851-35
Classification Flam. Liq. 3 - H226 STOT SE 3 - H335, H336 Asp. Tox. 1 - H304 Aquatic Chronic 2 - H411		

ZINC POWDER – ZINC DUST (STABILISED)		Content: <1%
CAS-No: 7440-66-6	EC No: 231-175-3	REACH Registration Number: 2119467174-37-xxxx
M factor (Acute) = 1 M factor (Chronic) = 1		
Classification Aquatic Acute 1 - H400 Aquatic Chronic 1 - H410		

The full text for all hazard statements are displayed in Section 16.

Section 4: First aid measures

4.1 Description of first aid measures

General information

Move the affected person to fresh air at once.

Inhalation

In case of inhalation of spray/mist: Move affected person into fresh air and keep warm and at rest in a position comfortable for breathing. If breathing stops, provided artificial respiration. Keep the affected person warm and at rest. Get medical attention immediately.

Ingestion

Rinse mouth thoroughly with water. Do not induce vomiting. Get medical attention.

Skin contact

Remove contaminated clothing immediately and wash skin with soap and water.

Eye contact

Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes and get medical attention.

4.2 Most important symptoms and effects, both acute and delayed

The severity of the symptoms described will vary dependent on the concentration and length of exposure.

4.3 Indication of any immediate medical attention and special treatment needed**Notes for the doctor**

Treat symptomatically.

Section 5: Firefighting measures**5.1 Extinguishing media****Extinguishing media**

Extinguish with foam, carbon dioxide, dry powder, or water fog.

5.2 Special hazards arising from the substance or mixture**Specific hazards**

Containers can burst violently or explode when heated, due to excessive pressure build-up. Vapours are heavier than air and may spread near the ground and travel a considerable distance to a source of ignition and flash back. Containers can burst violently or explode when heated, due to excessive pressure build-up. Extremely flammable. Forms explosive mixtures with air.

5.3 Advice for fire-fighters**Protective actions during firefighting**

Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Warn firefighters that aerosols are involved. Use water to keep fire exposed containers cool and disperse vapours.

Section 6: Accidental release measures**6.1 Personal precautions, protective equipment, and emergency procedures**

Use suitable respiratory protection if ventilation is inadequate. Avoid inhalation of vapours.

6.2 Environmental precautions

Avoid the spillage or runoff entering drains, sewers, or watercourses. Contain spillage with sand, earth, or any other suitable non-combustible material.

6.3 Methods and material for containment and cleaning up

Eliminate all sources of ignition. No smoking, sparks, flames, or other sources of ignition near spillage. Provide adequate ventilation. Leave small quantities to evaporate, if safe to do so. Do not allow material to enter confined spaces, due to the risk of explosion. Absorb spillage with non-combustible absorbent material.

6.4 Reference to other sections

For personal protection, see Section 8. For waste disposal, see Section 13.

Section 7: Handling and storage

7.1 Precautions for safe handling

Read and follow manufacturer's recommendations. Keep away from heat, sparks, and open flame. Eliminate all sources of ignition. Do not spray on a naked flame or any incandescent material.

7.2 Conditions for safe storage, including any incompatibilities

Keep away from heat, sparks, and open flame. Store at moderate temperatures in dry, well ventilated area. Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

7.3 Specific end use(s)

The identified uses for this product are detailed in Section 1.2

Section 8: Exposure control / personal protection

8.1. Control parameters

Occupational exposure limits

PETROLEUM GASES, LIQUEFIED; PETROLEUM GAS	Long-term exposure limit (8-hour TWA): WEL 1000 ppm 1750 mg/m ³ Short-term exposure limit (15 minute): WEL 1250 ppm 2180 mg/m ³
ACETONE	Long-term exposure limit (8-hour TWA): WEL 500 ppm 1210 mg/m ³ Short-term exposure limit (15 minute): WEL 1500 ppm 3620 mg/m ³
SOLVENT NAPHTHA (PETROLEUM), LIGHT AROM.; LOW BOILING PONT NAPHTHA	Long-term exposure limit (8-hour TWA): SUP 600 mg/m ³ Long-term exposure limit (8-hour TWQ): WEL 50 ppm
ZINC POWDER – ZINC DUST (STABILISED)	Long-term exposure limit (8-hour TWA): WEL 4 mg/m ³ respirable dust WEL = Workplace Exposure Limit

Ingredient Exposure Limits

WEL = Workplace Exposure Limit.

SOLVENT NAPHTHA (PETROLEUM), LIGHT AROM.; LOW BOILIN POINT NAPHTHA (CAS: 64742-95-6)

DNEL Industry, workers - Inhalation; Long term systemic effects: 150 mg/m³
Consumer - Inhalation; Long term systemic effects : 32 mg/m³

ZINC POWDER – ZINC DUST (STABILISED) (CAS: 7440-66-6)

DNEL Workers - Dermal; systemic effects: 83 mg/kg/day
Workers - Inhalation; systemic effects: 5 mg/m³
Consumers - Oral; systemic effects: 83 mg/kg/day
Consumers - Dermal; systemic effects: 83 mg/kg/day
Consumers - Inhalation; systemic effects: 2.5 mg/kg/day

PNEC Fresh water; 20.6 µg / l
Marine water; 6.1 µg / l
Sediment (Freshwater); 117.8 mg/kg
Sediment (Marine water); 56.5 mg/kg
Soil; 35.6 mg/kg

8.2 Exposure controls

Appropriate engineering measures

Provide adequate ventilation. Avoid inhalation of vapours and spray/mist. Observe any occupational exposure limits for the product or ingredients.

Personal protection

Do not eat, drink, or smoke when using this product.

Eye / face protection

Eyewear complying with an approved standard should be worn if a risk assessment indicates any eye contact is possible. The following protection should be worn: Chemical splash goggles.

Hand protection

Due to the packaging form, aerosol, risk of skin contact is small. Chemical-resistant imperious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. The most suitable glove must be chosen in consultation with the gloves supplier/manufacturer, who can inform about the breakthrough time of the glove material.

Hygiene measures

Wash hands after handling. Wash promptly if skin becomes contaminated. Wash hands at the end of each work shift and before eating, smoking, and using the toilet. Use appropriate skin cream to prevent drying of skin.

Respiratory protection

If ventilation is inadequate, suitable respiratory protection must be worn.

Section 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance	Aerosol
Colour	Silver
Odour	Organic solvents. Xylene
Initial boiling point and range	-40 to -2°C @ 1013 hPa
Flash point	< -40°C
Upper / lower flammability or explosive limits	Lower: 1.8% - Upper 9.5%
Vapour pressure	ca. 590 to 1760 kPa @ 45°C
Vapour density	ca. 1.5 @15°C
Auto Ignition Temperature	410 - 580°C
Comments	Information given is applicable to the major ingredient

9.2 Other information

This product contains a maximum VOC content of 662 g/l.

Section 10: Stability and reactivity

10.1 Reactivity

Stable at normal ambient temperatures and when used as recommended.

10.2 Chemical stability

Avoid heat, sparks, and flames.

10.3 Possibility of hazardous reactions

Does not decompose when used and stored as recommended.

10.4 Conditions to avoid

Avoid heat, flames, and other sources of ignition. Avoid exposing aerosol containers to high temperatures or direct sunlight.

10.5 Incompatible materials

Keep away from oxidising materials, heat, and flames.

10.6 Hazardous decomposition products

Does not decompose when used and stored as recommended. Thermal decomposition or combustion products may include the following substances: Toxic and corrosive gases or vapours.

Section 11: Toxicological information

11.1 Information on toxicological effects

General information

Deliberately concentrating and inhaling the contents of this container is dangerous and can be fatal.

Inhalation

Harmful by inhalation. In high concentrations, vapours and aerosol mists have a narcotic effect and may cause headache, fatigue, dizziness, and nausea. Unconsciousness, possibly death.

Skin contact

Harmful if in contact with skin.

Eye contact

Irritating to eyes. Spray and vapour in the eyes may cause irritation and smarting. Repeated exposure may cause chronic eye irritation.

Acute and chronic health hazards

Arrhythmia, (deviation from normal heartbeat). Irritating to eyes. Irritating to skin. In high concentrations, vapours and aerosol mists have a narcotic effect and may cause headache, fatigue, dizziness, and nausea.

Route of exposure

Inhalation, skin and / or eye contact.

Target organs

Central nervous system. Respiratory system, lungs.

Medical symptoms

Arrhythmia, (deviation from normal heartbeat). Narcotic effect. Vapours may cause drowsiness and dizziness. Skin irritation. Irritation of eyes and mucous membranes.

Section 12: Ecological information

Ecotoxicity

The product components are not classified as environmentally hazardous. However, large, or frequent spills may have hazardous effects on the environment.

12.1. Toxicity

Not available.

12.2. Persistence and degradability

Not available.

12.3. Bioaccumulative potential

Not available.

12.4. Mobility in soil

Not known.

12.5. Results of PBT and vPvB assessment

Not available.

12.6. Other adverse effects

Not available.

Section 13: Disposal considerations

13.1. Waste treatment methods

General information

Do not puncture or incinerate even when empty.

Disposal methods

Dispose of waste to licensed waste disposal sites in accordance with the requirements of the local Waste Disposal Authority. Containers should be thoroughly emptied before disposal because of the risk of explosion. Empty containers must not be punctured or incinerated because of the risk of explosion.

Section 14: Transport information

General This product is packed in accordance with the Limited Quantity Provisions of CDGCPL2, ADR and IMDG. These provisions allow transport of aerosols of less than 1 litre packed in cartons of less than 30kg gross weight to be exempt from control providing that they are labelled in accordance with the requirements of these regulations to show that they are being transported as Limited Quantities. Aerosols not so packed and labelled must show the following:

14.1 UN Number

UN No. (ADR/RID/ADN) 1950

UN No. (IMDG) 1950

UN No. (ICAO) 1950

14.2 UN proper shipping name

Proper shipping name (ADR/RID) AEROSOLS

Proper shipping name (IMDG) AEROSOLS (contains solvent naphtha (petroleum), light arom.; low boiling point naphtha, zinc powder - zinc-dust (stabilised)

Proper shipping name (ICAO) AEROSOLS

Proper shipping name (ADN) AEROSOLS

14.3 Transport Hazard Class(es)

ADR/RID class 2.1

ADR/RID classification code 5F

ADR/ADR label 2.1

IMDG class 2.1

ICAO Class / division 2.1

Transport labels**14.4 Packaging group**

Not applicable

14.5 Environmental hazards

Environmentally hazardous substance / marine pollutant

14.6 Special precautions for user

EmS F-D, S-U

Tunnel restriction code (D)

14.7 Transport in bulk according to Annex 11 of MARPOL and the IBC Code

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable

Section 15: Regulatory information**15.1. Safety, health, and environmental regulations/legislation specific for the substance or mixture****National Regulations**

Control of Substances Hazardous to Health Regulations 2002 (as amended).

EH40/2005 Workplace exposure limits.

The Aerosols Dispensers Regulations 2009 (SI 2009 No. 2824)

The Carriage of Dangerous Goods and Use of Transportable Pressure Equipment Regulations 2009.

(SI 2009 No. 1348) (as amended) CDG2009

EU legislation

Commission Regulation (EU) No. 2015/830 of 28 May 2015.

Guidance

Workplace Exposure Limits EH40.

Safety Data Sheets for Substances and Preparations.

Approved Classification and Labelling Guide (Sixth edition) L131.

British Aerosol Manufacturers Code of Practice 7th Edition 1999**15.2. Chemical Safety Assessment**

No chemical safety assessment has been carried out.

Section 16: Other information**Revision comments** Supplemental information added. Revised formulation. Revised classification.**Revision date** 2 April 2020**Revision** 6**SDS No.** 11777**SDS Status** Approved

Hazard Statements in Full

- H220 Extremely flammable gas.
- H222 Extremely flammable aerosol.
- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H229 Pressurised container; may burst if heated
- H280 Contains gas under pressure; may explode if heated.
- H304 May be fatal if swallowed and enter airways
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- H411 Toxic to aquatic life with long lasting effects.

Disclaimer

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.