


Data sheet | Item number: 2273-203

COMPACT PUSH WIRE® connector for junction boxes; 3-conductor terminal block; transparent housing; orange cover



www.wago.com/2273-203



Data

Electrical data

Ratings per IEC/EN 60664-1

Rated voltage (II / 2)	450 V
Rated impulse voltage (II / 2)	4 kV
Rated current	24 A
Legend (ratings)	(II / 2) ≙ Overvoltage category II / Pollution degree 2

Connection data

Connection technology	PUSH WIRE®
Actuation type	Push-in
Connectable conductor materials	Copper
Solid conductor	0.5 ... 2.5 mm ² / 18 ... 14 AWG
Strip length	11 mm / 0.43 Inch
Total number of connection points	3
Total number of potentials	1
Type of wiring	Side-entry wiring

Geometrical Data

Width	14 mm / 0.551 in
Height	5.8 mm / 0.228 in
Depth	16.7 mm / 0.657 in

Material Data

Color	orange
Cover color	orange
Flammability class per UL94	V2
Fire load	0.019 MJ
Weight	1.017 g


Environmental Requirements

Surrounding air (operating) temperature	60 °C
Continuous operating temperature up to	105 °C
T-Marking per EN 60998	T60



Commercial data

Country of Origin	DE
GTIN	4050821027850
Product Group	7 (Push Wire Conn.)

Country specific Approvals

Logo	Approval	Certificate name
	VDE VDE Prüf- und Zertifizierungsinstitut	40029794

Ship Approvals

Logo	Approval	Certificate name
	ABS American Bureau of Shipping	15-HG1419918-PDA
	DNV GL Det Norske Veritas, Germanischer Lloyd	TAE000015T

Subject to changes.

WAGO Kontakttechnik GmbH & Co. KG
Hansastr. 27
32423 Minden
Phone: +49571 887-0 | Fax: +49571 887-169
Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?
We are always happy to take your call at 01788 568 008.