

Product data sheet

Characteristics

SPH20

bending spring - heavy gauge - for 20 mm conduit



Main

Range of product	Mita
Product or component type	Bending spring
Product specific application	Heavy duty
Quantity per set	Set of 1

Complementary

Product destination	Diameter: 20 mm conduit
---------------------	-------------------------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.000 cm
Package 1 Width	3.000 cm
Package 1 Length	58.000 cm
Package 1 Weight	351.000 g
Unit Type of Package 2	CAR
Number of Units in Package 2	50
Package 2 Height	10.000 cm
Package 2 Width	14.000 cm
Package 2 Length	64.000 cm
Package 2 Weight	25.000 kg
Unit Type of Package 3	PAM
Number of Units in Package 3	1800
Package 3 Height	115.000 cm
Package 3 Width	120.000 cm
Package 3 Length	100.000 cm
Package 3 Weight	900.000 kg

Offer Sustainability

RECh Regulation	RECh Declaration
RECh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.