



### Main

Product name	TRK
Product or component type	Stop end
Colour tint	White
Quantity per set	Set of 5

### Complementary

Trunking dimension	75 x 50 mm
Fixing mode	Snap-fitted
Material with surface finish	UPVC (unplasticized polyvinyl chloride)

### Environment

Ambient air temperature for operation	-5...60 °C
---------------------------------------	------------

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.500 cm
Package 1 Width	5.000 cm
Package 1 Length	7.300 cm
Package 1 Weight	15.000 g
Unit Type of Package 2	BB1
Number of Units in Package 2	5
Package 2 Height	6.000 cm
Package 2 Width	8.500 cm
Package 2 Length	12.000 cm
Package 2 Weight	76.000 g
Unit Type of Package 3	CAR
Number of Units in Package 3	750
Package 3 Height	38.000 cm
Package 3 Width	51.000 cm
Package 3 Length	58.000 cm
Package 3 Weight	12.440 kg

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
RoHS exemption information	<a href="#">Yes</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	No need of specific recycling operations