



Main

Range of product	Mita
Product name	Ultimate 60 Ultimate 62 Cableline 40 Cableline 50
Product or component type	Mounting box
Colour tint	White
Quantity per set	Set of 10

Complementary

Trunking dimension	150 x 60 mm 180W x 52 mm 145W x 40 mm 180 x 52 mm 180V x 52 mm 145V x 40 mm 145 x 40 mm 190 x 62 mm
Number of gangs	1 gang
Mounting support	Trunking
Device mounting	Flush
Material	UPVC (unplasticized polyvinyl chloride)
Depth	25 mm

Environment

Standards	EN 50085-1: 2005 EN 50085-2-1
Ambient air temperature for operation	-5...60 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.6 cm
Package 1 Width	8.7 cm
Package 1 Length	8.0 cm
Package 1 Weight	35.0 g

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes

China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations