



### Main

Range of product	Mita
Product name	Cableline 50 Ultimate 60 Cableline 40 Ultimate 62
Product or component type	Mounting box
Colour tint	White
Quantity per set	Set of 10

### Complementary

Trunking dimension	145V x 40 mm 145 x 40 mm 180V x 52 mm 150 x 60 mm 180W x 52 mm 145W x 40 mm 180 x 52 mm 190 x 62 mm
Number of gangs	2 gangs
Mounting support	Trunking
Device mounting	Flush
Material	UPVC (unplasticized polyvinyl chloride)
Depth	25 mm

### Environment

Standards	EN 50085-1: 2005 EN 50085-2-1
Ambient air temperature for operation	-5...60 °C

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.600 cm
Package 1 Width	8.700 cm
Package 1 Length	14.200 cm
Package 1 Weight	52.000 g
Unit Type of Package 2	CAR
Number of Units in Package 2	10
Package 2 Height	18.000 cm
Package 2 Width	23.500 cm
Package 2 Length	18.000 cm
Package 2 Weight	624.000 g
Unit Type of Package 3	PAM
Number of Units in Package 3	1200
Package 3 Height	106.500 cm
Package 3 Width	120.000 cm

Package 3 Length	100.000 cm
Package 3 Weight	94.880 kg

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
RoHS exemption information	<a href="#">Yes</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	No need of specific recycling operations