



### Main

Range of product	Mita
Product or component type	Cable cleat
Product specific application	Heavy duty
Colour tint	Black
Quantity per set	Set of 50

### Complementary

Number of holes	1
Material	LDPP (low-density polypropylene)


### Environment

Environmental characteristic	UV resistant Impact resistant Corrosion resistance High strength
Ambient air temperature for operation	-35...85 °C

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	1.8 cm
Package 1 Width	2.7 cm
Package 1 Length	4.2 cm
Package 1 Weight	10 g

### Offer Sustainability

EU RoHS Directive	Not applicable, out of EU RoHS legal scope
Environmental Disclosure	 <a href="#">Product Environmental Profile</a>
Circularity Profile	No need of specific recycling operations

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.