## INS55301

## 87 mm mounting plate - twin switched socketoutlet (DE)



Main	
Range	Mita
Product or component type	Mounting plate
Accessory / separate part category	Mounting accessory
Type of floor	Raised floor
Floor box shape	Rectangular
Device presentation	Equipped
Colour tint	Blue (RAL 5003)
Quantity per set	Set of 1

Complementary	/
---------------	---

o in promortion y	
Range compatibility	Mita mounting plate
Product destination	3 compartments floor outlet box
Socket-outlet type	Twin switched socket-outlet conforming to BS 1363 13 A dual earth
Material	PA (polyamide) 6 Sheet steel
Thickness	1.2 mm
Length	173 mm
Width	87 mm
Depth	32 mm
[In] rated current	13 A at 230 V AC
Connections - terminals	Screw terminal

## Environment

IP degree of protection	IP20
Ambient air temperature for operation	-2560 °C

## **Packing Units**

r doking office	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	8.6 cm
Package 1 Width	3 cm
Package 1 Length	17.2 cm
Package 1 Weight	250.5 g
Unit Type of Package 2	CAR
Number of Units in Package 2	20
Package 2 Height	24 cm
Package 2 Width	18 cm
Package 2 Length	19.5 cm
Package 2 Weight	5.05 kg
Unit Type of Package 3	PAM
Number of Units in Package 3	2400
Package 3 Height	112.5 cm
Package 3 Width	100 cm
Package 3 Length	120 cm
Package 3 Weight	626 kg

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not inherenced as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the documentation is not be used to perform the appropriate and complete risk analysis, evaluation of the products with respect to the relevant specific application or use thereof. Neither Schmeider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Not applicable, out of EU RoHS legal scope