



# **MASTER PL-C 4 Pin**

# **MASTER PL-C 10W/840/4P 1CT/5X10BOX**

Energy-saving compact fluorescent lampsCompact long-arc low-pressure mercury discharge lampEnvelope consists of 4 parallel narrow fluorescent tubes

#### **Warnings and Safety**

- Lamp light technical and electrical characteristics are influenced by operating conditions, i.e. lamp ambient temperature and operating position as well as applied HF control gear
- Shorter lamp life when often switching and not well pre-heated electrodes
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

#### **Product data**

General Information	
Cap base	G24Q-1 [ G24q-1]
Life to 50% failures preheat (nom.)	13000 h
LSF preheat 2,000 hours rated	99 %
LSF preheat 4,000 hours rated	98 %
LSF preheat 6,000 hours rated	97 %
LSF preheat 8,000 hours rated	90 %
Light Technical	
Colour Code	840 [ CCT of 4,000 K]
Luminous flux (nom.)	600 lm
Luminous flux (rated) (nom.)	600 lm
Colour designation	Cool White (CW)
Correlated Colour Temperature (Nom)	4000 K
Luminous efficacy (rated) (nom.)	60 lm/W
Colour rendering index (nom.)	82
LLMF 2000 h Rated	92 %

LLMF 4000 h Rated	87 %
LLMF 6000 h Rated	83 %
LLMF 8000 h Rated	81 %
Operating and Electrical	
Power (Rated) (Nom)	10.0 W
Lamp current (nom.)	0.190 A
Temperature	
Design temperature (nom.)	28 ℃
Controls and Dimming	
Dimmable	Yes
Mechanical and Housing	
Cap-base information	4P


Datasheet, 2021, April 15 data subject to change

# **MASTER PL-C 4 Pin**

Approval and Application	
Energy efficiency label (EEL)	A
Mercury (Hg) content (nom.)	1.4 mg
Energy consumption kWh/1,000 hours	11 kWh
Product Data	
Full product code	871150062330070
Order product name	MASTER PL-C 10W/840/4P 1CT/5X10BOX
EAN/UPC – product	8711500623300

Order code	62330070
Local order code	10PLC8404PIN
SAP numerator – quantity per pack	1
Numerator – packs per outer box	50
SAP material	927907084040
SAP net weight (piece)	41.400 g
ILCOS code	FSQ-10/40/1B-E-G24q=1


# Dimensional drawing




PL-C 10W/840/4P

# Product D (max) D1 (max) A (max) B (max) C (max) MASTER PL-C 10W/840/4P 27.1 mm 75.5 mm 95.0 mm 109.9 mm 1CT/5X10BOX

#### Photometric data




Lightcolour /840




Lightcolour /840

# **MASTER PL-C 4 Pin**

#### Lifetime





LDLE\_PLC4P\_0001-Life expectancy diagram

LDLE\_PLC4P\_0002-Life expectancy diagram



LDLM\_PLC4P\_0001-Lumen maintenance diagram



© 2021 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.