Product datasheet Characteristics

1208016 Spring Toggle Cavity fixing





Main

| | | · · |
|---------------------------|----------------|--------------|
| Range of product | Thorsman | ကို |
| Product or component type | Cavity fixing | ي |
| Product name | Thorsman TOG | |
| Device short name | TOG | 20 |
| Provided equipment | Screw | t d |
| Mounting support | Board material | <u>```</u> } |
| Device application | board material | |
| Mounting support | Wall mounted | |
| Thread type | M3 | # |
| Screw diameter | 3 mm | |
| Screw length | 50 mm | |
| Drilling diameter | 11 mm | |
| Colour tint | Metal | |
| | | 0 |

Complementary

| Quantity per set | Set of 50 |
|-------------------------------|-----------|
| Sale per indivisible quantity | 50 |

Environment

| Material | Screw: steel electroplated Cavity fixing: sheet metal electroplated | |
|------------------------------|---------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Practical load capacity | Pull-out load: 100 N for 13 mm plasterboard | Tinger Ti |
| Thickness | 030 mm fixture | . <u>s</u> |
| Environmental characteristic | Fire resistance | ation— |

Offer Sustainability

| onor odotamasinty | | ĕ |
|--------------------------|-----------------------|----|
| Sustainable offer status | Green Premium product | i. |

| REACh Regulation | REACh Declaration | |
|----------------------------|------------------------------------------------------------------------------------------|--|
| REACh free of SVHC | Yes | |
| EU RoHS Directive | Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration | |
| Toxic heavy metal free | Yes | |
| Mercury free | Yes | |
| RoHS exemption information | Yes | |
| China RoHS Regulation | China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope) | |
| Environmental Disclosure | Product Environmental Profile | |

Contractual warranty

| Warranty | 18 months |
|----------|-----------|