Product datasheet Characteristics

GMC13SSPF

Exclusive Metal clad - switched fused connection - grey



Aesthetic name	Metal clad	
Product or component type	Switched fused connection	
Switch function	Switch	
Colour tint	Grey	

Complementary

itched fused connection itch ey nout neon indicator ang wder coated steel II mounted screws A at 230 V AC ew terminals of 10 mm mm mm
nout neon indicator ang wder coated steel Il mounted screws A at 230 V AC rew terminals of 10 mm mm
nout neon indicator ang wder coated steel II mounted screws A at 230 V AC rew terminals of 10 mm mm
ang wder coated steel II mounted screws A at 230 V AC rew terminals of 10 mm mm
ang wder coated steel II mounted screws A at 230 V AC rew terminals of 10 mm mm
wder coated steel Il mounted screws A at 230 V AC rew terminals of 10 mm mm
Il mounted screws A at 230 V AC rew terminals of 10 mm
screws A at 230 V AC rew terminals of 10 mm mm
A at 230 V AC rew terminals r of 10 mm
rew terminals of 10 mm mm
of 10 mm mm
mm mm
mm
mm
0
1363
mpliant RoHS Declaration
5
5
ina RoHS declaration induct out of China RoHS scope. Substance declaration for your information

Environment

2. Trinorimone				
IP degree of protection	IP20			
Standards	BS 1363			

Offer Sustainability

EU RoHS Directive	Compliant EU RoHS Declaration	
Mercury free	Yes	
RoHS exemption information	Yes	;
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information	_

Warranty 18 months