Product datasheet Characteristics

GGBL6012CS

Lisse - Universal dimmer - 1 gang - 2 way - 400W/VA



		۷.
Range	Lisse	
Aesthetic name	White moulded	
Product or component type	Dimmer	
Device presentation	Complete product	
Load type	230 V AC halogen lamp Incandescent lamp: 400 W	, and a second s
Colour tint	White matt	
Quantity per set	Set of 1	4

Complementary

Device mounting	Wall mounted	<u>}</u>
Dimmer application	Inductive load Resistive load	
[Ue] rated operational voltage	230 V AC 50 Hz	
Number of gangs	1 gang	<u> </u>
Connections - terminals	Screw terminals	
Fixing mode	By screws M3.5 x 25 mm	d
Material	Urea (carbamide)	
Type of packing	Bag	<u>ة</u> .
Height	87 mm	
Width	87 mm	<u>च</u> <u>द</u>
Depth	43.6 mm	
Net weight	0.072 kg	Ū n
-		

Environment

Standards	BS EN 60669-2-1	<u> </u>
IP degree of protection	IP20	it.

Offer Sustainability

		: -
REACh Regulation	REACh Declaration	بز خ

REACh free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty	18 months