Product datasheet Characteristics

GGBL5013S

Lisse - 13A Fuse connection unit with Flex Outlet frame





Main

Range	Lisse	
Aesthetic name	White moulded	
Product or component type	Fuse connection unit	
Device presentation	Complete product	
Colour tint	white moulded	
Quantity per set	Set of 1	

Complementary

· · · · · · · · · · · · · · · · · ·		
Pilot light	without LED	
Actuator	Rocker	
Number of gangs	1 gang	
Material	Urea (carbamide)	7
Device mounting	Wall mounted	9
Fixing mode	By screws	÷
Rated current	13 A at 250 V AC	<u>.</u>
Connections - terminals	Screw terminals	j.
Type of packing	Bag	
Width	87 mm	2
Height	87 mm	0
Depth	25 mm	, de la companya de l
Net weight	0.092 kg	<u></u>

Environment

Standards	BS 1363
IP degree of protection	IP20

Offer Sustainability

Sustainable offer status	Green Premium product	
REACh Regulation	REACh Declaration	
REACh free of SVHC	Yes	
EU RoHS Directive	Compliant EU RoHS Declaration	
Toxic heavy metal free	Yes	
Mercury free	Yes	
RoHS exemption information	Yes	
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)	
Environmental Disclosure	Product Environmental Profile	
Circularity Profile	ity Profile End of Life Information	

Contractual warranty

Warranty	18 months	