



## Main

|                           |                  |
|---------------------------|------------------|
| Product or component type | Ceiling switch   |
| Device presentation       | Complete product |
| Colour tint               | White            |
| Quantity per set          | Set of 10        |

## Complementary

|                         |                    |
|-------------------------|--------------------|
| Switch function         | 2-pole 1-way       |
| Control type            | Rocker             |
| Number of gangs         | 1 gang             |
| Pilot light             | Red neon indicator |
| Device mounting         | Ceiling            |
| Rated current           | 6 AX at 230 V AC   |
| Connections - terminals | Screw terminals    |
| Material                | Urea (carbamide)   |
| Surface finish          | Matt               |
| Height                  | 86 mm              |
| Width                   | 86 mm              |
| Depth                   | 50 mm              |
| Net weight              | 0.116 kg           |

## Environment

|                         |               |
|-------------------------|---------------|
| Standards               | BS EN 60669-1 |
| IP degree of protection | IP20          |

## Offer Sustainability

|                            |  |
|----------------------------|--|
| EU RoHS Directive          | Compliant<br><a href="#">EU RoHS Declaration</a> |
| Mercury free               | Yes  |
| RoHS exemption information | <a href="#">Yes</a>                              |
| China RoHS Regulation      | <a href="#">China RoHS declaration</a>           |

### Contractual warranty

---

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|

---