

# ADA182U

RCBO Electronic 1P 10kA C Curve-32A, 30mA Type A(AC & Pulsating DC Sensitive)1M



- Architecture
  - Neutral position right
  - Number of poles 1 P
  - Type of pole 1 P
  - Curve C
- Main electrical features
  - Rated operational voltage  $U_e$  230 / 240 V
  - Frequency 50 Hz
  - Rated current 32 A
- Voltage
  - Rated insulation voltage 250 V
  - Max operating voltage 253 V
  - Rated impulse withstand voltage 4000 V
- Electric current
  - Rated residual operating current 30 mA
  - Breaking and opening capacity

- 6 kA
- Electric current / temperature
  - Rating current 30°C  
32 A
- Dimensions
  - Depth of installed product  
70 mm
  - Height of installed product  
115 mm
  - Width of installed product  
17.8 mm
- Power
  - Total power loss under IN  
9.63 W
- Endurance
  - Electric endurance in number of cycles  
2000
  - Number of mechanical operations  
1000
- Capacity
  - Number of modules  
1
- Installation, mounting
  - Tightening torque  
2,1Nm
- Standards
  - Standard text  
EN 61009-1 ; IEC 61009-1
  - European directive WEEE  
concerned
- Safety
  - Protection index IP  
IP20
  - Residual current type  
A
- Temperature
  - Operating temperature  
-5/60 °C