



**Description**

Rejiband® steel bracket suitable for wall installation of the Rejiband® 60 mm high and 60 mm wide wire mesh tray. Used for ceiling installation together with threaded rod. Quick assembly thanks to the Click system of connection without screws. Made of steel, finished in electrogalvanised EG.

**Advantages**

Fixing by quick mount click system.

Suitable for ceiling installation using an M8 threaded rod. It allows easy adjustment on the rod and only requires a nut for fixing.

Can be used for ceiling installations with two rejiband trays using a bracket on each side of the tray.

It allows the introduction of cables into the tray from the side.

Electrogalvanised finish (standard EN-ISO 2081), silver colour, suitable for indoor installations. Corrosion resistance class 3.

**Applications**

Suitable for wall and ceiling mounting with threaded rod of Rejiband® wire mesh tray 60 mm wide and widths of 100 and 150. Suitable for electrical and telecommunication installations in public buildings, infrastructures and civil works, industrial installations, tertiary sector.

**Solutions**



**Product data**

<b>Finish</b>	E.G.	<b>Resistance Class</b>	Class 3
<b>Fire Resistance</b>	A1 No combustible	<b>SWL (kg)</b>	25
<b>kg/u</b>	0.042	<b>u</b>	25 u
<b>Material</b>	Steel with surface coating	<b>Working temperature range (°C)</b>	-50°/ 150°

**Coatings**

**PG/GS** - Pre-Galvanised Finish. Resistance to corrosion according to EN-10346. Adequate for indoor installations.

**EZ** - Electrogalvanized, white, according to EN ISO 2081. Electrolytic zinc protection adequate for indoor installations.

**BC** - Electrogalvanized Bycro, yellow, in compliance with EN ISO 2081. Improved resistance to corrosion, especially adequate for demanding indoor installations.

**GC** - Hot-dipped galvanizing in compliance with EN ISO 1461. Appropriate for outdoor installations and aggressive environments.

**BLACK C8** - High Resistance coating, Black Colour. Neutral Salt Spray Chamber test >1000 h acc. to ISO 9227.

**304 and 316L** stainless steel, in compliance with EN 10088 standard, with passivated Thermicron treatment. Appropriate for outdoor installations and highly aggressive environments.



**Product applications**

□ □ □ □

