



**Description**

Light duty support used for the wall and ceiling installation of the Rejiband® wire mesh tray in 35 and 60 mm depth and 60 mm width. Quick assembly thanks to the Click system of connection without screws. Made of steel, finished in electrogalvanised EG.

**Advantages**

Fast mount system without the need for screws. Folding the fixing clips secures the tray.

For wall installation, use the side holes to secure with a M6 or M8 screw or bolt.

For ceiling installation, use M6 or M8 threaded rod connected through the centre of the bracket.

It allows the introduction of cables into the tray from the side.

Electrogalvanised finish (standard EN-ISO 2081), silver colour, suitable for indoor installations. Corrosion resistance class 3.

**Applications**

Suitable for wall and ceiling mounting of the Rejiband® 35x60 and 60x60 mm wire mesh tray.

**Solutions**



**Product data**

<b>Finish</b>	E.G.	<b>Resistance Class</b>	Class 3
<b>Fire Resistance</b>	A1 No combustible	<b>u</b>	10 u
<b>kg/u</b>	0.066	<b>Working temperature range (°C)</b>	-50°/ 150°
<b>Material</b>	Steel with surface coating		

**Coatings**

**PG/GS** - Pre-Galvanised Finish. Resistance to corrosion according to EN-10346. Adequate for indoor installations.

**EZ** - Electrogalvanized, white, according to EN ISO 2081. Electrolytic zinc protection adequate for indoor installations.

**BC** - Electrogalvanized Bycro, yellow, in compliance with EN ISO 2081. Improved resistance to corrosion, especially adequate for demanding indoor installations.

**GC** - Hot-dipped galvanizing in compliance with EN ISO 1461. Appropriate for outdoor installations and aggressive environments.

**BLACK C8** - High Resistance coating, Black Colour. Neutral Salt Spray Chamber test >1000 h acc. to ISO 9227.

**304 and 316L** stainless steel, in compliance with EN 10088 standard, with passivated Thermicron treatment. Appropriate for outdoor installations and highly aggressive environments.



**Product applications**

□

