



Description

Metal clip for connecting Rejiband® wire mesh tray tray to 41x21 or 41x41 mm channel and strut. The clip fastening is compatible with all types of channel. It is suitable for all tray sizes except 35x60 and 60x60 mm.

Advantages

Fixing by quick mount click system.

No screws or other fasteners required.

Hot dip galvanised finish (standard UNE-EN ISO 1461), suitable for outdoor installations and in aggressive environments. Corrosion resistance class 6.

Applications

Suitable for the fast fixing of Rejiband wire mesh tray onto 41x21 or 41x41 channel in interior installations in a dry atmosphere without contaminants, outdoor, industrial, marine, rural or aggressive Interior installations.

Solutions



INDUSTRIA PETROQUÍMICA TUNELES. INFRAESTRUCTURAS



Product data

Finish	H.D.G.	Resistance Class	Class 5
Fire Resistance	A1 No combustible	u	50 u
kg/u	0.016	Working temperature range (°C)	-50°/ 150°
Material	Steel with surface coating		

Coatings

PG/GS - Pre-Galvanised Finish. Resistance to corrosion according to EN-10346. Adequate for indoor installations.

EZ - Electrogalvanized, white, according to EN ISO 2081. Electrolytic zinc protection adequate for indoor installations.

BC - Electrogalvanized Bycros, yellow, in compliance with EN ISO 2081. Improved resistance to corrosion, especially adequate for demanding indoor installations.

GC - Hot-dipped galvanizing in compliance with EN ISO 1461. Appropriate for outdoor installations and aggressive environments.

BLACK C8 - High Resistance coating, Black Colour. Neutral Salt Spray Chamber test >1000 h acc. to ISO 9227.

304 and 316L stainless steel, in compliance with EN 10088 standard, with passivated Thermicron treatment. Appropriate for outdoor installations and highly aggressive environments.



Product applications

□ □ □

