

## Tel: 0845 094 0244

Fax: 0845 094 0255

www.securiflex.co.uk

sales@securiflex.co.uk

## SFX/6C-TY3-PVC-BLK

6 Core TCCA Type 3 Alarm Cable Black PVC to BS4737-3.30:2015



Cable Construction	6 Cores
Conductor	Tinned Copper Clad Aluminium
Conductor Diameter (mm)	0.20 ±0.008 x 7
Stranded Diameter (mm)	0.61
Insulation	PVC
Insulation Thickness (mm)	0.21
Insulation Diameter (mm)	1.00 ±0.100
Insulation Colours	Red,Black,Blue,Yellow,Green,White
Nylon Rip-Cord	Yellow 210D
Jacket	PVC
Jacket Thickness (mm)	0.50
Overall Diameter (mm)	4.00 ±0.200
Jacket Colour	Black RAL 9005
Sheath Printing	(m)
Reaction to Fire	Eca
Electrical Characteristics	
Max Conductor DC resistance @ 20°C	155Ω/km
Rated Temperature	80°C
Rated Voltage	30V
Insulation Resistance @20°C	>200 MΩ/km



www.securiflex.co.uk

Every care is taken to ensure all information in this publication is correct. No Legal responsibility can be accepted for any inaccuracy. The company reserves the right to alter or modify the information of this specification without notice. E&OE. Registered in England & Wales, Company No.03758330. VAT Number: 736 5084 24