


LED Lowbay

- Slim profile Lowbay, ideal energy saving replacement for traditional HID fittings
- Ultra efficient up to 130 Lumen/Watt
- Superbly reliable MEANWELL ELG driver 1-10V dimmable as standard
- Latest LED technology: PHILIPS Lumileds
- Pure aluminium heatsink, Polycarbonate cover lens
- Beam spread: 120°
- Wire suspension fixing kit included
- IP Rating: IP20
- Colour temperature: 5000k
- Colour rendering index: >80
- Rated Life: 50,000 hours
- Operating temperature: -40°C to 50°C
- Options available:
 - Surface mounting bracket kit
 - Microwave Sensor kit
 - Sensor programming handset



Part No.	Description	Wattage	Measurement L x W x H	Weight	Dimmable Function	Lumen Output	IP Rating	Colour Temperature
Lowbay								
LXLB100WCW	LED Lowbay 120° - White	100W	579 x 245 x 59mm	3.0Kg	1-10V	13000Lm	IP20	5000K
LXLB150WCW	LED Lowbay 120° - White	150W	579 x 359 x 59mm	4.1Kg	1-10V	19500Lm	IP20	5000K
LXLB200WCW	LED Lowbay 120° - White	200W	579 x 359 x 59mm	4.3Kg	1-10V	26000Lm	IP20	5000K
Bracket								
LXLB-BMK	Bracket Mounting Kit	2 x Brackets, 8 x Screws kit - For direct to surface or trunking mounting						
Microwave Sensor								
LXLB-MSW-RC	Microwave Sensor - White	Direct to Lowbay mounting - Motion and Daylight sensor, IP65, 1-10V dimmable, max. 15m mounting height						
LXLB-RC	Remote Control Handset	Programmable remote control handset for use with LXLB-MSW-RC Sensor						



Email sales@luxna.co.uk



Web luxna-lighting.com