

Emergency Bulkhead 3W LE

Ideal for all industrial and commercial emergency lighting applications. Open areas, escape routes and exits.

- 3 hour emergency maintained or non-maintained operation
- Polycarbonate base and impact • resistant diffuser
- Hinged gear tray for quick installation
- Push-fit terminal connector
- 20mm conduit entry points: Top, side and rear
- Manufactured in accordance to: BS EN 60598-2-22
- 3W LED, 120 Lumen (AC) ٠
- IP Rating: IP65
- Colour temperature: 6000k ٠
- Colour rendering index: >80
- Rated Life: 30,000 hours
- Operating temperature: -5°C to 40°C •
- Supplied with universal legend kit as standard
- Legend viewing distance: 18m
- Battery: Ni-Cd 3.6V 1200mAh •
- Options available:
 - Semi-recessing mounting kit
 - Universal self-adhesive legend kit







Part No.	Description	Wattage	Measurement L x W x H	Lumen Output	Viewing Distance	IP Rating	Colour Temperature
LXEBH	Emergency Bulkhead LED	3W	350x110x60mm	120Lm	18m	IP65	6000K
Accessories							
LXEBH/RK	Recessing Kit	-	395x255x156mm	Semi-recessing kit including spring clip fixings			
LXEBH/LK	Universal Legend Kit	_	-	Self adhesive ISO pictograms to configure Up, Down, Left or Right direction			



