

# Emergency Exit Box 4W LED

Ideal for all industrial and commercial emergency lighting applications. Open areas, escape routes and exits.

- 3 hour emergency maintained or non-maintained operation
- Robust steel housing and interchangeable polycarbonate legend panels
- Diffuser panel on base for additional downward illumination
- 20mm conduit entry points: Top and rear
- Manufactured in accordance to: BS EN 60598-2-22
- 4W LED
- IP Rating: IP20
- Colour temperature: 6000k
- Colour rendering index: >80
- Rated Life: 30,000 hours
- Operating temperature: -5°C to 40°C
- Supplied with ISO pictogram legend as standard: Arrow Up
- Legend maximum viewing distance: 34m
- Battery: Ni-Cd 3.6V 1200mAh
- Options available:
  - ISO directional pictogram polycarbonate legends: Arrow Up, Arrow Down, Arrow Right, Arrow Left



**3 YEAR WARRANTY**
**LED**
**IP20**
**EM3 EMERGENCY 3 Hour Duration**

Part No.	Description	Wattage	Measurement W x H x D	Viewing Distance	IP Rating	Colour Temperature
LXEEB	Emergency Exit Box LED	4W	390x190x60mm	34m	IP20	6000K
<b>Accessories</b>						
LXEEB/L/AU	Legend Arrow Up	-	385x185x2mm	34m	Polycarbonate ISO pictogram - Direction Up	
LXEEB/L/AD	Legend Arrow Down	-	385x185x2mm	34m	Polycarbonate ISO pictogram - Direction Down	
LXEEB/L/AR	Legend Arrow Right	-	385x185x2mm	34m	Polycarbonate ISO pictogram - Direction Right	
LXEEB/L/AL	Legend Arrow Left	-	385x185x2mm	34m	Polycarbonate ISO pictogram - Direction Left	



Email [sales@luxna.co.uk](mailto:sales@luxna.co.uk)



Web [luxna-lighting.com](http://luxna-lighting.com)