

LED Wall Pack Slim

Slimline decorative Wall Pack, ideal energy saving replacement for fluorescent 2D

- Black polycarbonate base and detachable front trim
- Opal polycarbonate impact resistant diffuser
- IP Rating: IP65
- IK Rating: IK08
- Colour temperature: 4000k
- Colour rendering index: >80
- Rated Life: 30,000 hours
- Operating temperature: -10°C to 40°C
- Surface fixing and cable gland kit included
- Dimensions: Length 305mm, Width 255mm, Height 101mm
- Photocell: 10-20 Lux On / 30-60Lux Off
- Options available:
 - Integral Photocell Sensor
 - Integral 3 Hour Emergency
 - Integral Photocell Sensor and 3 Hour Emergency



3 YEAR
WARRANTY

LED

IP65


Photocell

EM3 EMERGENCY MAINTAINED 3 HOURS

Part No.	Housing Colour	Photocell	Emergency EM3	Wattage	Measurement L x W x H	Lumen Output	IP Rating	Colour Temperature
LXWPS	Black	No	No	22W	305 x 255 x 101mm	1500Lm	IP65	4000K
LXWPS/PC	Black	Yes	No	22W	305 x 255 x 101mm	1500Lm	IP65	4000K
LXWPS/EM3	Black	No	Yes	22W	305 x 255 x 101mm	1500Lm	IP65	4000K
LXWPS/EM3/PC	Black	Yes	Yes	22W	305 x 255 x 101mm	1500Lm	IP65	4000K



Email sales@luxna.co.uk



Web luxna-lighting.com