

## LED Panel 600

### UGR <19 Low Glare

What is UGR<19 – A luminaire which has a ‘Unified Glare Rating’ of 19 or less is suitable for use in applications where low glare lighting is required and areas where ‘visual comfort’ may be critical.

- High luminaire efficacy, 100 Lumen/Watt
- Low glare, optical pattern diffuser for even light distribution
- ECA compliant, 33W = 3300Lm
- Standard non dimmable driver included
- 4000K colour temperature
- Colour rendering index >0.80
- Suitable for 25mm and 15mm T-bar ceilings
- Frame colour: White
- Energy savings up to 60% when replacing 4x18W T8 luminaires
- Options available:
  - Dimmable driver 1-10v & DALI: **LXLPF2-30D-48**
  - Emergency 3hr remote pack: **LXLPF2-60-EM3**
  - Surface mounting frame: **LXPAN66SMB**
  - Wire suspension kit: **LXPAN663SCK**
- Ideal for: Offices, health care, education, museums and galleries, retail, laboratories, logistics and industry.



Part No.	Wattage	Measurements L x W x H	Lumen Output	Colour Temperature	UGR Rating
LXPAN33LED66NW2/UGR19	33W	595 x 595 x 10.5mm	3300Lm	4000K NW	<19