

Product Code: CL011

Description: 10AX 1 Gang 2 Way Plate Switch



General Information

Dimensions	80mm (W) x 80mm (H) x 42mm (D)	
Finish	Metal Clad Grey	
Insert Colour	White (WH)	
Materials	Front Plate & Mounting Box: Electrophoretically Coated Steel	Insert & Rocker Switch: Urea
	Rear Housing: Nylon	Terminals: Brass
	Terminal Screws: Steel & Yellow Passivated	Contacts: Silver "on-lay" Copper / Brass
	Internal Busbars: Formed Pressed Brass	Earth Strap: Mild Steel
Maximum Voltage	250V~ 50Hz	
Load Rating	10AX (Suitable for Inductive Loads)	
Plate Fixing Centres	60.3mm	
Terminal Size	3.5mmø	
Terminal Torque	0.5Nm	
Terminal Capacity	4 x 1.5mm ² or 2 x 2.5mm ²	
Two Way	Yes	
Back Box Depth	40mm Supplied	
Termination Type	Screw	
Earth Terminal Provided	Yes	
Back Box Knockouts	5 x 20mm (2 on top, 1 on bottom, 1 on each side)	
Operational Temperature	-5°C to +40°C	
Warranty	10 Years	
Standards	BS EN 60669-1:1999 +A1:2002 +A2:2008	

Additional Information

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal. Interchangeable with modules in the MiniGrid Range. Module colour to match is Click White (WH)

