



Product Code: CL022

Luckinslive 389086376

Description: 20A Double Pole Plate Switch With Optional Flex Outlet



General Information

Dimensions (mm)	80 (W) x 80 (H) x 42 (D)	
Plate Fixing Centres - Horizontal (mm)	60,3	
Style	Metal Clad	
Colour	Grey	
Insert Colour	White	
Materials	Front Plate & Mounting Box: Electrophoretically Coated Steel	Insert, Switch & Rear Housing: Urea
	Terminals: Brass	Terminal Screws: Steel & Yellow Passivated
	Contacts: Silver "on-lay" Copper / Brass	Internal Busbars: Formed Pressed Brass
	Earth Strap: Mild Steel	
Operating Voltage (AC)	250	Frequency (Hz) 50
Resistive Load Rating (A)	20	
Termination Type	Screw	
Terminal Size (mm)	Ø5	Terminal Torque Value (Nm) 1.8
Terminal Capacity - Solid (mm²)	3 x 2,5	
Double Pole Switch	Yes	
Twin Earth Terminals	Yes	
Flex Outlet Available	Yes	
Flex Outlet Location	Front of Plate	Flex Outlet Dimension (mm) Ø10
Supplied Back Box Depth (mm)	40	
Back Box Knockouts - Total (mm)	5 x Ø20	
Back Box Knockouts - Top (mm)	2 x Ø20	Back Box Knockouts - Bottom (mm) 1 x Ø20
Back Box Knockouts - Rear (mm)	None	Back Box Knockouts - Sides (mm) 1 x Ø20
Back Box Earth Terminal Supplied	Yes	
Ingress Protection	IP20	
Operational Temperature (°C)	-5 to +40	
Warranty (Years)	20	

Standards BS EN 60669-1

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.
Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.



CLICK OR SCAN

Catalogue



Range



DoC



Installation



CLICK OR SCAN