

**Product Code:** CL051

**Description:** 13A Double Pole Switched Fused Connection Unit With Optional Flex Outlet



### General Information

<b>Dimensions</b>	80mm (W) x 80mm (H) x 42mm (D)	
<b>Finish</b>	Metal Clad Grey	
<b>Materials</b>	Front Plate & Mounting Box: Electrophoretically Coated Steel	Insert, Switch, Fuse Drawer & Housing: Urea
	Terminals: Brass	Terminal Screws: Steel & Yellow Passivated
	Contacts: Silver "on-lay" Copper / Brass	Internal Busbars: Formed Pressed Brass
	Earth Strap: Mild Steel	
<b>Maximum Voltage</b>	250V~ 50Hz	
<b>Load Rating</b>	13A	
<b>Plate Fixing Centres</b>	60.3mm	
<b>Terminal Size</b>	5mmø	
<b>Terminal Torque</b>	2.0Nm	
<b>Terminal Capacity</b>	3 x 2.5mm <sup>2</sup> or 2 x 4mm <sup>2</sup>	
<b>Switched</b>	Yes	
<b>Double Pole</b>	Yes	
<b>Twin Earth Terminals</b>	Yes	
<b>Fuse Fitted</b>	13A (BS 1362)	
<b>Flex Outlet</b>	Yes (10mmø Through Front of the Plate)	
<b>Back Box Depth</b>	40mm Supplied	
<b>Termination Type</b>	Screw	
<b>Earth Terminal Provided</b>	Yes	
<b>Back Box Knockouts</b>	5 x 20mm (2 on top, 1 on bottom, 1 on each side)	
<b>Operational Temperature</b>	-5°C to +40°C	
<b>Warranty</b>	10 Years	
<b>Standards</b>	BS 1363-4: 2016 +A1: 2018 BS 1362:1973	

### Additional Information

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.  
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.