



Product Code: CL105

Luckinslive 389086554

Description: 10AX 6 Gang 2 Way Plate Switch



General Information

Dimensions (mm)	140 (W) x 80 (H) x 42 (D)	
Plate Fixing Centres - Horizontal (mm)	120.6	
MiniGrid Plate (Gang)	2	
MiniGrid Single Width Module Quantity	2 x 3	
MiniGrid Double Width Module Quantity	2	
Style	Metal Clad	
Colour	Grey	
Insert Colour	White	
Materials	Front Plate & Mounting Box:	Insert & Switch: Urea
	Electrophoretically Coated Steel	Terminals: Brass
	Rear Housing: Urea	Contacts: Silver "on-lay" Copper / Brass
	Terminal Screws: Steel & Yellow Passivated	Earth Strap: Mild Steel
	Internal Busbars: Formed Pressed Brass	Frequency (Hz) 50
Operating Voltage (AC)	250	
Inductive Load Rating (AX)	10	
Load Rating Comments	Suitable for Fluorescent or Inductive Loads	
Termination Type	Screw	
Terminal Size (mm)	Ø3,5	Terminal Torque Value (Nm) 0.5
Terminal Capacity - Solid (mm²)	4 x 1.5 or 2 x 2.5	
Modular Rocker Switches	Yes	
2 Way Switch	Yes	
Supplied Back Box Depth (mm)	40	
Back Box Knockouts - Total (mm)	7 x Ø20	
Back Box Knockouts - Top (mm)	3 x Ø20	Back Box Knockouts - Bottom (mm) 2 x Ø20
Back Box Knockouts - Rear (mm)	None	Back Box Knockouts - Sides (mm) 1 x Ø20
Back Box Earth Terminal Supplied	Yes	
Ingress Protection	IP20	
Operational Temperature (°C)	-5 to +40	
Warranty (Years)	20	

Standards BS EN 60669-1

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth. Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product. Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

Interchangeable with modules in the MiniGrid Range. Module colour to match is Click White (WH)



CLICK OR SCAN

Catalogue



Range



DoC



Installation



CLICK OR SCAN