



Product Code: CL202

Luckinslive 389086606

Description: 45A 2 Gang (Vertical) Double Pole Plate Switch



**General Information**

Dimensions (mm)	80 (W) x 140 (H) x 52 (D)		
Plate Fixing Centres - Vertical (mm)	120.6		
Style	Metal Clad		
Colour	Grey		
Insert Colour	White		
Materials	Front Plate & Mounting Box: Electrophoretically Coated Steel	Insert, Switch & Rear Housing:	Urea
	Terminals: Brass	Terminal Screws:	Steel & Yellow Passivated
	Contacts: Silver "on-lay" Copper / Brass	Internal Busbars:	Formed Pressed Brass
	Earth Strap: Mild Steel		
Operating Voltage (AC)	250	Frequency (Hz)	50
Resistive Load Rating (A)	45		
Termination Type	Screw		
Terminal Size (mm)	Ø6	Terminal Torque Value (Nm)	2.5
Terminal Capacity - Solid (mm²)	1 x 16		
Double Pole Switch	Yes		
Twin Earth Terminals	Yes		
Product Marking	On & Off		
Supplied Back Box Depth (mm)	50		
Back Box Knockouts - Total (mm)	7 x Ø20		
Back Box Knockouts - Top (mm)	3 x Ø20	Back Box Knockouts - Bottom (mm)	2 x Ø20
Back Box Knockouts - Rear (mm)	None	Back Box Knockouts - Sides (mm)	1 x Ø20
Back Box Earth Terminal Supplied	Yes		
Ingress Protection	IP20		
Operational Temperature (°C)	-5 to +40		
Warranty (Years)	20		

**Standards** BS EN 60669-1

**Additional Information**

For cleaning / polishing of products, use only a soft, dry, clean cloth.  
 Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.  
 Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.



CLICK OR SCAN

Catalogue



Range



DoC



Installation



CLICK OR SCAN