


Product Code: CMA013

Description: 10AX 3 Gang 2 Way Plate Switch



### General Information

<b>Dimensions</b>	86mm (W) x 86mm (H) x 9.5mm (D)	
<b>Plate Design &amp; Finish</b>	Rounded Profile Polar White	
<b>Materials</b>	Front Plate & Rocker Switch: Urea	Rear Housing: Nylon
	Terminals: Brass	Terminal Screws: Steel & Yellow Passivated
	Contacts: Silver "on-lay" Copper / Brass	Internal Busbars: Formed Pressed Brass
<b>Maximum Voltage</b>	250V~ 50Hz	
<b>Load Rating</b>	10AX (Suitable for Inductive Loads)	
<b>Plate Fixing Centres</b>	60.3mm	
<b>Terminal Size</b>	3.5mm $\varnothing$	
<b>Terminal Torque</b>	0.5Nm	
<b>Terminal Capacity</b>	4 x 1.5mm <sup>2</sup> or 2 x 2.5mm <sup>2</sup>	
<b>Two Way</b>	Yes	
<b>Ingress Protection</b>	IP20	
<b>Back Box Depth</b>	16mm Minimum	
<b>Termination Type</b>	Screw	
<b>Operational Temperature</b>	-5°C to +40°C	
<b>Warranty</b>	20 Years	
<b>Standards</b>	BS EN 60669-1:1999 +A1:2002 +A2:2008	

### Additional Information

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.  
 Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.  
 All white moulded accessories are manufactured using Urea Formaldehyde, which has similar inherent properties to antimicrobial additives that inhibit the growth of infectious diseases as well as anti-viral properties against enveloped and non-enveloped viruses.  
 All products have been independently tested with 99.9% of enveloped viruses and 92% of non-enveloped viruses killed off whilst achieving a 99.9% kill rate across all four types of the strains of bacteria - MRSA, E-Coli, Salmonella, and Klebsiella Pneumoniae.

Interchangeable with modules in the MiniGrid Range.