

Technical Specification

Description: 20A Double Pole Plate Switch With Optional Flex Outlet





General Information

Dimensions 86mm (W) x 86mm (H) x 9.5mm (D)

Plate Design & Finish Rounded Profile Polar White

Materials Front Plate & Rocker Switch: Urea

Terminals: Brass

Contacts: Silver "on-lay" Copper / Brass

Earth Strap: Mild Steel

Maximum Voltage 250V~ 50Hz

Load Rating 20A
Plate Fixing Centres 60.3mm
Terminal Size 5mmø
Terminal Torque 1.8Nm

Terminal Capacity 3 x 2.5mm²

Double Pole Yes

Twin Earth Terminals Yes

Flex Outlet Yes (10mmø Through Bottom of the Plate)

Ingress Protection IP20

Back Box Depth 25mm Minimum

Termination Type Screw

Operational Temperature -5°C to +40°C

Warranty 20 Years

Standards BS EN 60669-1:1999 +A1:2002 +A2:2008

Rear Housing: Urea

Terminal Screws: Steel & Yellow Passivated Internal Busbars: Formed Pressed Brass

Additional Information

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal. All white moulded accessories are manufactured using Urea Formaldehyde, which has similar inherent properties to antimicrobial additives that inhibit the growth of infectious diseases as well as anti-viral properties against enveloped and non-enveloped viruses.

All products have been independently tested with 99.9% of enveloped viruses and 92% of non-enveloped viruses killed off whilst achieving a 99.9% kill rate across all four types of the strains of bacteria - MRSA, E-Coli, Salmonella, and Klebsiella Pneumoniae.









Specification is subject to change without notice.