


**Product Code:** CMA156

**Description:** Non-Isolated Single Satellite Outlet



### General Information

<b>Plate Dimensions (mm)</b>	86 (W) x 86 (H) x 9.5 (D)
<b>Plate Fixing Centres - Horizontal (mm)</b>	60.3
<b>Style</b>	Rounded Profile
<b>Finish</b>	Polar White
<b>Materials</b>	Front Plate: Urea Terminals: Brass
<b>Anti Microbial Certified</b>	Yes
<b>Termination Type</b>	Screw
<b>Isolated</b>	No
<b>Non-Isolated</b>	Yes
<b>Non-Isolated Comments</b>	Enables 2 way signal transmission
<b>Shielded</b>	No
<b>Minimum Back Box Depth (mm)</b>	16
<b>Ingress Protection</b>	IP20
<b>Operational Temperature (°C)</b>	-5 to +40
<b>Warranty (Years)</b>	20

Earth Plate: Mild Steel

### Additional Information

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal. Isolated socket will filter out any interference, if a 2 way signal is required, i.e. for use with satellite hard wire extensions, then a non-isolated outlet is required.

All white moulded accessories are manufactured using Urea Formaldehyde, which has similar inherent properties to antimicrobial additives that inhibit the growth of infectious diseases as well as anti-viral properties against enveloped and non-enveloped viruses.

All products have been independently tested with 99.9% of enveloped viruses and 92% of non-enveloped viruses killed off whilst achieving a 99.9% kill rate across all four types of the strains of bacteria - MRSA, E-Coli, Salmonella, and Klebsiella Pneumoniae.

