

Technical Specification

Product Code: MD004WH

Description: 10AX 2 Way Retractive Switch Module



General Information

Dimensions (mm)	25 (W) x 53 (H) x 20 (D)		
Finish	Click White		
Materials	Rocker Switch:	Urea	
	Terminals:	Brass	
	Contacts:	Silver "on-lay" Copper / Brass	
Anti Microbial Certified	Yes	Rear Housing: Nylon	
Rated Voltage (V~) (Ue)	250	Terminal Screws: Steel & Yellow Passivated	
Inductive Load Rating (AX)	10	Internal Busbars: Formed Pressed Brass	
Load Rating Comments	Suitable for Inductive Loads		
Termination Type	Screw		
Terminal Size (mm)	Ø3.5	Frequency (Hz)	50
Terminal Capacity - Solid (mm²)	4 x 1.5 or 2 x 2.5	Terminal Torque Value (Nm)	0.5
Modular Rocker Switches	Yes		
2 Way Switch	Yes		
Retractive Contact Options	Press to Make or Break		
Minimum Back Box Depth (mm)	16 (25 Flat Plate)		
Operational Temperature (°C)	-5 to +40		
Warranty (Years)	10		
Standards	BS EN 60669-1		

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.
 Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.
 Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.
 Suitable and matches both the Deco white range and Metal Clad range.