

Product Code: MD023PW

Luckinslive 389103013

Description: 20A Double Pole Switch With Neon Module



General Information

Dimensions (mm)	41 (W) x 52.5 (H) x 22 (D)			
Colour	Polar White			
Materials	Rocker Switch:	Urea	Rear Housing:	Nylon
	Neon Cover:	Polycarbonate	Terminals:	Brass
	Terminal Screws:	Steel & Yellow Passivated	Contacts:	Silver "on-lay" Copper / Brass
	Internal Busbars:	Formed Pressed Brass		
Anti Microbial Certified	Yes			
Operating Voltage (AC)	250	Frequency (Hz)	50	
Resistive Load Rating (A)	20	Terminal Torque Value (Nm)	1.2	
Termination Type	Screw			
Terminal Size (mm)	Ø4.4			
Terminal Capacity - Solid (mm ²)	3 x 2.5 or 2 x 4			
Modular Rocker Switches	Yes			
Double Pole Switch	Yes			
Neon Indicator	Yes			
Minimum Back Box Depth (mm)	25 (35 Flat Plate)			
Operational Temperature (°C)	-5 to +40			
Warranty (Years)	20			
Indicator Colour	Orange			

Standards BS EN 60669-1

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.
 Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.
 Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

Suitable and matches the Definity, Mode, Polar & Part M ranges



CLICK OR SCAN

Catalogue



Range



DoC



CLICK OR SCAN