

Product Code: MM020WH

Description: 16A European Schuko Socket Outlet Module



**General Information**

Dimensions (mm)	50 (W) x 50 (H) x 40.1 (D)		
Finish	Polar White		
Materials	Cover & Housing: Polycarbonate	Terminals: Brass	
	Terminal Screws: Steel & Yellow Passivated	Internal Busbars: Formed Pressed Brass	
Anti Microbial Certified	No		
Rated Voltage (V~) (Ue)	250	Frequency (Hz)	50
Resistive Load Rating (A)	16		
Termination Type	Screw		
Terminal Size (mm)	Ø5	Terminal Torque Value (Nm)	2.5
Terminal Capacity - Solid (mm²)	3 x 2.5 or 2 x 4		
Minimum Back Box Depth (mm)	47		
Ingress Protection	IP20		
Operational Temperature (°C)	-5 to +40		
Warranty (Years)	1		

**Standards** IEC 60884

**Additional Information**

For cleaning / polishing of products, use only a soft, dry, clean cloth.  
 Accepts plug types C & F.  
 A 47mm (Metal Clad: 50mm) deep back box will be required.  
 Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.  
 Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

