


Product Code: VPSC413BK


Description: 10AX Ingot 3 Gang 2 Way Plate Switch



General Information

Dimensions	88mm (W) x 88mm (H) x 8mm (D)	
Dimensions With Gasket	91mm (W) x 91mm (H) x 9mm (D)	
Plate Design & Finish	Victorian Satin Chrome	
Insert & Gasket Colour	Black	
Materials	Front Plate: Stainless Steel Switch Cover: Stainless Steel Terminals: Brass Contacts: Silver "on-lay" Copper / Brass Earth Strap: Mild Steel	Insert: Urea Rear Housing: Nylon Terminal Screws: Steel & Yellow Passivated Internal Busbars: Formed Pressed Brass Gasket: Nylon
Maximum Voltage	250V~ 50Hz	
Load Rating	10AX (Suitable for Inductive Loads)	
Plate Fixing Centres	60.3mm	
Terminal Size	3.5mmø	
Terminal Torque	0.5Nm	
Terminal Capacity	4 x 1.5mm ² or 2 x 2.5mm ²	
Two Way	Yes	
Ingress Protection	IP20	
Back Box Depth	16mm Minimum	
Termination Type	Screw	
Operational Temperature	-5°C to +40°C	
Warranty	10 Years	
Standards	BS EN 60669-1:1999 +A1:2002 +A2:2008	

Additional Information

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.
Interchangeable with modules in the MiniGrid Range. 

UK Design Registration: 3015621