

Product Code: PRC009

Description: 10AX 2 Way Pull Cord Switch



### General Information

<b>Dimensions</b>	76mm Diameter x 51.5mm
<b>Finish</b>	Polar White
<b>Materials</b>	Cover & Pattress: Urea Terminal Housing: Urea Terminals: Brass Terminal Screws: Steel & Yellow Passivated Internal Busbars: Formed Pressed Brass Earth Strap: Mild Steel Pull Bell: Urea
<b>Maximum Voltage</b>	250V~ 50Hz
<b>Load Rating</b>	10AX (Suitable for Inductive Loads)
<b>Terminal Size</b>	4mmø
<b>Terminal Torque</b>	0.4Nm
<b>Terminal Capacity</b>	2 x 1.5mm <sup>2</sup> or 1 x 2.5mm <sup>2</sup>
<b>Twin Earth Terminals</b>	No
<b>Ingress Protection</b>	IP20
<b>Back Box Depth</b>	Supplied
<b>Back Box Knockouts</b>	4 x 12mm x 9mm and 1 x 17mm x 23mm
<b>Operational Temperature</b>	-5°C to +40°C
<b>Warranty</b>	20 Years
<b>Standards</b>	BS EN 60669-1:1999 +A1:2002 +A2:2008

### Additional Information

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.  
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.  
All white moulded accessories are manufactured using Urea Formaldehyde, which has similar inherent properties to antimicrobial additives that inhibit the growth of infectious diseases.  
All products have been independently tested and achieved a 99.9% kill rate across all four types of the strains of bacteria - MRSA, E-Coli, Salmonella, and Klebsiella Pneumoniae.